STATE OF NEW MEXICO MERGY AND MINERALS DEPARTMENT

MB. OF COPICS RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.\$.G.\$.	
LAND OFFICE	
OPERATOR	

APPROVED BY CONDITIONS OF APPROVAL, IF ANY

OIL CONSERVATION DIVISION P. O. BOX 2088

SANTA FE. NEW MEXICO 87501

Form C-103 Revised 10-1-78

SANTA PE, NEW MEXICO 87501	
FILE	5a. Indicate Type of Lease
U.\$.0.\$.	State K Fue
LAND OFFICE	5. State Oil & Gas Lease No.
OPERATOR	V-48
SUNDRY NOTICES AND REPORTS ON WELLS TO NOT USE THIS FORM FOR PROPOSALS TO DRILL ON TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.	
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	A Linux Associate Name
·	7. Unit Agreement Name
OIL X GAS WELL OTHER-	
1. Name of Operator	8. Farm or Lease Name
MORRIS R. ANTWEIL	State SX
. Address of Operator	9. Well No.
Box 2010, Hobbs, New Mexico 88240	1
Location of Well	10. Field and Pool, or Wildcat
J 1980 FEET FROM THE SOUTH LINE AND 1980 FEET FROM	Undesignated
UNIT LETTER FEET FROM THE LINE AND FEET FRO	mmmmmm [*]
THE East LINE, SECTION 36 TOWNSHIP 19-S RANGE 37-E NMPP	· (()
	11 Comment HARAIN
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3595 ' GR	. Lea ////////
Check Appropriate Box To Indicate Nature of Notice, Report or O	ther Data
•••	IT REPORT OF:
PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
The state of the s	PLUG AND ABANDONMENT
TEMPORARILY ABARDON	
CHANGE PLANS CASING TEST AND CEMENT JOB A	
OTHER	
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	ng estimated date of starting any proposed
work) SEE RULE 1103.	
a 11 1 7 20 7 10 7 11 1001 Prilled 12 1/4" hold	2 +0 1500'
Spudded 7:30 AM 10 April, 1981. Drilled 12-1/4" hole	20 1300 .
Ran 38 jts. $8-5/8$ " $24\#$ J-55 casing and cemented @ 150	JO with 450 sx.
Halliburton Lite Cement containing 5#/sx. gilsonite,	1/4#/sx Flocele
and 2% CaCl2 and 300 sx. Class "C" cement containing	2% CaCl ₂ . Plug
down @ 4:30 AM 11 April, 1981. Circulated 100 sx. ce	
down & 4:50 AM II April, 1501. Streathers for SA. or	ut and drilling
Tested casing to 2000 psi - 30 mins - OK. Drilled on	ut and driffing
ahead W/ 7-7/8" bit.	
•	
·	
•	
·	
i8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
· · · · · · · · · · · · · · · · · · ·	
Emwillion Agent	DATE 20 April 1981
SICHED TITLE THE	
- Company of the comp	. The section of the section of
Facility (Maxima)	APR 22 1981
TITLE TITLE	DATE

TITLE ___