

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other

2. NAME OF OPERATOR  
Superior Oil Company, The

3. ADDRESS OF OPERATOR  
P. O. Box 3901, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 1980' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(other)		

5. LEASE  
NM-13644A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Featherstone Federal

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Featherstone

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 21, T-20-S; R-35-E

12. COUNTY OR PARISH  
Lea

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3716' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Loaded hole with 9.5# gelled brine. 12-11-84
2. Set 7-5/8" C.I.B.P. at 5250' and capped with 50' (5 sacks) cement plug by Gearhart Wireline on 12-13-84.
3. Cut off 7-5/8" casing at 4632'. Pulled and laid down all 7-5/8" casing above cut.
4. Spotted 75 sack Class C cement from 4680' to 4631', on 12-13-84. W.O.C. 3 hrs. and tagged plug at 4631'.
5. Spotted 75 sack Class C cement plug from 4471' to 4371', on 12-13-84. W.O.C. 3 hrs and tagged plug at 3371'.
6. Spotted 65 sack cement plug from 720' to 520'. Tagged cement plug at 520'.
7. Spotted 35 sack cement plug from 90' to surface on 12-13-84.
8. Cut off well head 6' below ground level and welded steel plate on top of casing. Installed dry hole marker. WELL PLUGGED & ABANDONED 12-14-84

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED G.E. Tate G.E. Tate TITLE Div. Operations Supt. DATE 12-17-84

Orig. Sgd. Under U.S. Seal (This space for Federal or State office use)

APPROVED BY Acary Anna Alonzo TITLE \_\_\_\_\_ DATE 3-20-87

CONDITIONS OF APPROVAL, IF ANY:

**RECEIVED**

**MAR 23 1981**

**OCD**

**HOBBS OFFICE**