Form Approved. Budget Bureau No. 42-R1424

UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	NM 13644-A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas well other	Featherstone Federal 9. WELL NO.
2. NAME OF OPERATOR THE SUPERIOR OIL COMPANY	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P.O. Box 4500 The Woodlands, Texas 77380	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1980' FNL & 1980' FEL, Sec. 21,	Sec. 21, T20S-R35E
AT SURFACE: 1980' FNL & 1980' FEL, Sec. 21, AT TOP PROD. INTERVAL: T20S-R35E AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE Lea New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3716' GR
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Set casing	8 1007E: Report results of multiple completion or zone chadge on Form 9-330.) CAS
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine Drilled with rotary rig as of 0700, 8-25-81. run casing. Ran 15 joints of 16", 65#, H-40 with 731 sx Class "C" w/2% CaCl2 and 1/4#/sx to surface.	nt to this work.)* Circulated and conditioned to , ST&C. Set 16" casing at 628'
•	
•	
Subsurface Safety Valve: Manu. and Type	Set @ Ft
18. I hereby certify that the foregoing is true and correct	
	TOUD DATE September 4, 1981
G. Bannant incular MAN (This space for Federal or State o	
APPROVED BY CFE CONDITIONS OF APPROVAL, JE ANY	DATE

CC: UUSOSE (DEDZ) IC ADWHURWAS, BJW, GLS, LDM, RG, CF
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

*See Instructions on Reverse Side