OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

[ ] [X]

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

[ ] FEE [X] STATE OTHER

Name of Operator: Doyle Hartman

Address of Operator: P. O. Box 10426, Midland, Texas 79702

Lease Name: Ellen Weir

Well No.: 1

Location of Well: UNIT LETTER M 660 FEET FROM THE South LINE AND 330 FEET FROM THE West LINE, SECTION 3, TOWNSHIP 20S, RANGE 37E, NMPM

Elevation (Show whether DF, RT, GR, etc.): 3549.7 G.L.

Pool: Eumont (Gas)

County: Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK [ ]
- TEMPORARILY ABANDON [ ]
- PULL OR ALTER CASING [ ]
- PLUG AND ABANDON [ ]
- CHANGE PLANS [ ]
- OTHER [ ]

SUBSEQUENT REPORT OF:

- REMEDIAL WORK [ ]
- COMMENCE DRILLING OPNS. [ ]
- CASING TEST AND CEMENT JOB [X]
- OTHER [ ]
- ALTERING CASING [ ]
- PLUG AND ABANDONMENT [ ]

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled well to a total depth of 3950'. Ran 90 joints (3953.14') of 7" OD, 23 lb/ft, J-55, ST&C casing and landed at 3950' RKB. Cemented casing with 250 sx of API Class-C cement containing 3% Econolite 1/2 lb/sx Floseal and 5 lb/sx Gilsonite followed by 300 sx of a 50-50 blend of API Class-C cement and Pozmix "A" containing 9 lb/sx salt and 1/2 lb/sx Floseal. Plug down at 5:15 p.m. 12-13-81. Pressure tested casing to 1500 psi. Released rig at 3:30 a.m. 12-14-81.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Michelle Hernandez TITLE Administrative Assistant DATE 12-15-81

Approved by
Jerry Sexton
Supervisor, District I

APPROVED BY TITLE DATE 1981

CONDITIONS OF APPROVAL, IF ANY: