

UNIT STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLY  
(Other instructions  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.  
DESIGNATION AND SERIAL NO.

NOV 05 1982

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

Ike Lovelady, Inc.

3. ADDRESS OF OPERATOR

P.O. Drawer 2666; Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

660' FNL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

Gr 3555.3'

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

MEXICO 83240

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sam H. Snoddy Fed.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 26, TWP-20-S, R-32-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) finish drilling & run 5-1/2" X  
(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/1/82 to

9-2-82 Drilled 8-3/4" hole to 13,480'

9/3/82

Ran open hole logs. Comp. Formation Density, Dual Laterlog, Sonic. All logs from 13,470' back to 5200'.

9/4/82 to

9/8/82 Ran 5-1/2" Csg. 17#, N-80 & 20# N-80. Set @ 13,480'. D.V. Tool @ 10,795'. Cement bottom stage W/250 Sks Howco lite, (cir. 20 Sks Cement) & 400 Sks 50/50 Poz mix. Cement 2nd stage W/500 Sks 50/50 Poz Mix. Plug down @ 3:00 A.M. 9/8/82. Tested Csg. to 1500#.

9/9/82

Ran temp. survey top cement 8400'. Rig down Drlg. rig.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Mgr. of Drlg. & Prod.

DATE 10/6/82

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY  
CONDITIONS OF APPROVAL

TITLE

DATE

OCT 13 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

RECEIVED

OCT 14 1982

G.C.C.  
HOBBS OFFICE