

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases owned or leased by the State agency, or having jurisdiction over Federal and/or State lands and regulations. Any necessary special instructions concerning the use of this form and its attachments may be found in the accompanying with regard to land area or regional procedures in completion, either are shown below or will be issued by or may be obtained from the local Federal, State, or County agency. See instructions on items 22 and 24 and 33 below regarding separate reports for separate completions.

Item 1: To the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, etc.) as well as formation logs, logs, and directional surveys, should be attached hereto to the extent required by applicable Federal and/or State laws and regulations. All attachments shall be listed on this form, see item 33.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which completion is used as reference, where not otherwise shown, for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completions), so state in item 22 and in item 24 show the producing interval, or intervals, top(s), bottom(s), and name(s) of any, for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement" Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

31. SUMMARY OF FORGUS ZONES				32. GEOLOGIC MARKERS		
SHOW ALL IMPORTANT ZONES, TOP, BOTTOM, AND CONTENTS THEREOF. CORED INTERVALS, AND ALL COMPLETION TESTS, INCLUDING DEPTH, INTERVAL TESTED, CIRCULATION USED, TIME TOOL OPEN, FLOWING, AND SHUT-IN PRESSURE, AND RECOVERIES				TOP		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VEST. DEPTH
Triassic-Permian	0	1100	Red Beds			
Rustler	1100	3006	Anhydrite, Shale, & Salt			
Tansill	3006	3196	Anhydrite & Dolomite			
Yates	3196	3410	Sandstone, Shale, Dolomite, & Anhy.			
Goat Seep Capitan Rf.	3410	5230	Dolomite W/Sandstone in lower section	Rustler	1100	1100
Delaware	5230	7897	Sandstone	Tansill	3006	3006
Bone Spring	7897	8966	Limestone	Yates	3196	3196
1st Bone Spring Sd.	8966	9519	Sandstones W/some Limestone & Shale	Goat Seep Cap. Rf.	3410	3410
2nd " " "	9519	10,594	Sandstones & Limestone W/some Shale	Delaware	5230	5230
			(Limestone from 10,535-551 was not tested but put oil into mud system until well reached total depth.)	Bone Spring	7897	7897
3rd " " "	10,594	11,285	Limestone & Sands W/some shale	1st BS. Sd.	8966	8966
Wolfcamp	11,285	11,906	Limestone W/Shales and Sands	2nd BS. Sd.	9519	9519
Strawn	11,906	12,080	Limestone W/some Shale	3rd BS. Sd.	10,594	10,594
Atoka	12,080	12,523	Limestone grading down to Sands & Shale	Wolfcamp	11,285	11,285
Morrow Lime	12,523	12,963	Limestone W/some Shale & Sand	Strawn	11,906	11,906
Morrow Clastic	12,963	13,419	Alternating Sand & Shale W/some Limestone	Atoka	12,080	12,080
Barnett	13,419	13,480-TD	Dr. Gray Siltstone-Shale	Morrow Lime	12,523	12,523
				Morrow Clastic	12,963	12,963
				Barnett	13,419	13,419

BEST AVAILABLE COPY