well

below.)

AT SURFACE:

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

REPORT, OR OTHER DATA

ABANDON*
(other) Run 5½" csg & cement

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE **CHANGE ZONES**

Form Approved. Budget Bureau No. 42-91424

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)

other

P.O. Box 806 Eunice, New Mexico 88231 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,

2615' FNL & 1980' FWL

gas

well

Anadarko Production Company

	THE BUILDER IN TENTE		
5.	LEASE LC - 064975		
6.	IF INDIAN, ALLOTTEE OR TRIBE NAME		
7.	UNIT AGREEMENT NAME Teas Yates Unit		
8.	FARM OR LEASE NAME Tract # 2		
9.	WELL NO.		
10.	FIELD OR WILDCAT NAME Teas		
11.	SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 13, Twp 20S, rg 33E		
12.	COUNTY OR PARISH 13. STATE Lea NM		
14.	API NO.		
15.	ELEVATIONS (SHOW DF, KDB, AND WD)		

NOTE: Report esults of multiple completion or zone

19827 change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1. Resumed drlg @ 1:00 PM 3-28-83 w/9-7/8" bit.
- 2. Drilled 9-7/8" hole to 3210, @ 11:30 PM 3-31-83.

XXUBSEQUENT R

- 3. Ran 57 jts (2449') of 7-5/8" new 29.70#, S-95, LT&C Rg 3 csg & 18 jts (758') of 7-5/8" new 26.40#, K-55, ST&C Rg 3 csg w/float collar & guide shoe.
- 4. Pumped 1050 sx Halliburton Lt. cement w/15# salt per sx & 2% CACL. Followed w/200 sx Class "C" Neat cement. Plug down @ 10:10 AM 4-1-83. Circ 230 sx to pit. Released drlg rig @ 1:15 PM.
- 5. Moved in Cable Tools to drill through Yates zone 4-7-83.

Subsurface Safety Valve: Manu. and Typ	De	Set @ Ft.
18. I hereby certify that the foregoing is riginal signed by	true and correct TITLE Field Foreman DAT	re May 4, 1983
	(This space for Federal or State office use)	
APPROVED BY	TITLE	ACCEPTED FOR RECORD
	*See Instructions on Payarea Sida	JUL 1 3 1983

*See Instructions on Reverse Side