DISTRIBUTE BANTA FE FILE			CONSERVA P. O. BO. SANTA FE, NEW		S a. Indicate	Form C-103 Revised 10-1-78
U.S.G.S. LAND OFFICE DPERATOR					State Oi	Fee
SUNDRY NOTICES AND REPORTS ON WELLS						eement Name
with Operator	WELL X	07HER-				Lease Name
Alpha Twe			.omp any		Jo 9. Well No.	
	1200 Jal,	Vew Mexi	ico 88252		1 10, Field o	md Pool, or Wildcat
UNIT LETTER			PROM THE West		77777	ont Gas
South	LINE, SECTION			37-E	_ MAPM.	
		15. 8	Alevation (Show whether 3717.4 GR	DF, RT, GR, etc.)	12. County Lea	
	Check Ap			Nature of Notice, Report SUBS	rt or Other Data EQUENT REPORT	OF:
IFCAM FEMEDIAL WO			PLUG AND ABANDON	REMEDIAL WORK COMMENCE DRILLING OPHS.		ALTERING CASING PLUG AND ABANDONMENT
LE OR ALTER CABING	<u> </u>		CHANGE PLANS	CASING TEST AND CEMENT JQB	· 🗓	
OTHER	. []	(Class)		отнея		are of starting any proposed
OTHER DESCRIPTIONS OF THE PROPERTY OF THE PROP	d or Completed Oper		ly state all pertinent det	OTHER	including estimated d	
OTHER DESCRIPTIONS OF THE PROPERTY OF THE PROP	d or Completed Oper 1703. Ran 11 jts. 405.5 GR.	of 8-5/8	ly state all pertinent det	otherails, and give persinent dates, for surface. Total of Class 'C' with	including estimated depth was 418	S' KB or
OTHER DESCRIPTIONS OF THE PROPERTY OF THE PROP	d or Completed Oper 1103. Ran 11 jts. 405.5 GR. Flocele. C	of 8-5/8 Cement v	ly state all pertinent det 8" 23# casing f with 250 sacks d 80 sacks of c	otherails, and give persinent dates, for surface. Total of Class 'C' with	including estimated do depth was 418 2% CaCl ₂ and 7	S' KB or
Describe Proposed Work) SEE RULE	Ran 11 jts. 405.5 GR. Flocele. C Tested surf Ran 100 jts 3927.13 GR cement with with 325 sa Halad-4 and	of 8-5/8 Cement virculated ace casing Cement 15 lbs. cks of 5 $\frac{1}{2}$ " cks of 56	8" 23# casing f with 250 sacks d 80 sacks of c ng to 1000 psi 14# casing in t with a lead s salt, 5 lbs. 0 0/50 Pozmix Cla locele. Circul	otherails, and give pertinent dates, or surface. Total of Class 'C' with cement.	depth was 418 2% CaCl ₂ and 70%. That at 3939.73' of Halliburton Flocele; tares, 5 lbs. salt cement.	KB or KB or KB or International KB or Internat
Describe Proposed work) SEE RULE 1-7-83	Ran 11 jts. 405.5 GR. Flocele. C Tested surf Ran 100 jts 3927.13 GR cement with with 325 sa Halad-4 and	of 8-5/8 Cement wirculated ace casin Cement 15 lbs. cks of 56 4 lb. Find be pres	8" 23# casing f with 250 sacks d 80 sacks of c ng to 1000 psi 14# casing in t with a lead s salt, 5 lbs. (0/50 Pozmix Cla locele. Circul sure tested who	or surface. Total of Class 'C' with cement. for 30 minutes the hole. Pipe seclurry of 450 sacks dilsonite and \(\frac{1}{4}\) lb. ass 'C' with 2% gellated 125 sacks of en completion opera	depth was 418 2% CaCl ₂ and 700K. That 3939.73's of Halliburte Flocele; tailed, 5 lbs. salt cement.	KB or KB or KB or International KB or Internat

I hereby certify that the information above is true and complete to the best of my knowledge and belief. JAN 24 1983

355 127

MAR 30 1983 ACRES OFFICE