

C. CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-1  
Revised

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☐

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER- ☐

Name of Operator  
Alpha Twenty-One Production Company

Address of Operator  
P.O. Box 1206, Jal, NM 88252

Location of Well  
UNIT LETTER D 660 FEET FROM THE North LINE AND 660 FEET FROM  
West LINE, SECTION 9 TOWNSHIP 19-S RANGE 37-E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name

Oney

9. Well No.

1

10. Field and Pool, or Whichever

Eumont Gas

15. Elevation (Show whether DF, RT, GR, etc.)  
3693.3 GL

12. County  
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

APPROPRIATE REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐  
REPAIR OR ALTER CASING ☐ CHANGE PLANS ☐  
OTHER ☐

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDON ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER Casing and Cementing ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any work) SEE RULE 1103.

The well was spudded 5-11-83

Drilled 15" hole and set 30' of 12-3/4" Grade B Conductor Pipe and cemented with Redimix to surface.

Drilled 12-1/2" hole and ran 402.28' of 8-5/8", 23# Grade B Surface Casing and cemented with 250 sx Class "C", CACL2. Circulated 50 sx. (Work accomplished 5-12-83).

Drilled 7-7/8" hole and ran 3963.89' of 5-1/2", K-55, 15.50# Production Casing as follows: (20' above rotary table)

Float Shoe	1.65'	Pipe set @ 3943.89' KB
Shoe Joint	19.50'	
Float Collar	1.55'	
94 jts.	3941.19'	
Total	3963.89'	

Cement: (Work accomplished 5-19-83)

Lead Slurry: 600 sx HLC; Tail Slurry: 375 sx 50/50 Poz "H"; Circulated 176 sx

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Michael D. Oney  
Michael D. Oney  
ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT 1 SUPERVISOR

TITLE Drilling Superintendent

DATE May 25, 1983

MAY 31 1983

COPIES BY

TITLE

DATE

EDITIONS OF APPROVAL, IF ANY:

RECEIVED  
MAY 27 1983  
O.C.D.  
HOBBS OFFICE