

N. M. OIL CONS. COMMISSION
P. O. I. 1980
HOBBS, NEW MEXICO 88240
UNITED STATES

Form Approved.
Budget Bureau No. 42-R1424

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Harvey E. Yates Company

3. ADDRESS OF OPERATOR
P. O. Box 1933, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 330' FNL & 1650' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Ran & 1st Csg. Cmt Job

5. LEASE

NM-38467

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

West Lynch 30

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 30, T-20S, R-34E

12. COUNTY OR PARISH 13. STATE

Lea

NM

14. AP. NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3662.3 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 8/18/83 Spudded 12 1/4" hole @ 10:30 am 8/17/83. Ran 12 jts (493') 8 5/8", 24#, J-55 csg. Cmt @ 505' w/325 sxs Cl "C" 1/4# flocele & 2% CaCl. WOC 18 hrs, press test to 1000 psi - Held 0. K.
- 8/23/83 Ran 87 jts (3511') 5 1/2" 15#, J-55 LT&C 8rd csg & cmt @ 3500'. 1ST Stage: 175 sxs Howco Lite, 15# salt, 1/4# flocele. PD 1st stage @ 1:15 a.m. 8/23/83. 2nd Stage: 150 sxs Howco Lite 15# salt 1/4# flocele followed w/100 sxs Cl "C". PD 2nd Stage @ 6:00 a.m. 8/23/83.
- 8/24/83 Ran Temp Survey - showed TOC @ 560'. 1" to surface w/175 sxs Cl "C" neat; Circ 10 sx to surface.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Reservoir Engineer DATE August 31, 1983

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 7 1983