

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fed <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator Amoco Production Company		8. Farm or Lease Name South Hobbs (GSA) Unit	
3. Address of Operator P. O. Box 68, Hobbs, New Mexico 88240		9. Well No. 144	
4. Location of Well SL/BHL UNIT LETTER M 580/1310 FEET FROM THE South LINE AND 775/1310 FEET FROM THE West LINE, SECTION 3 TOWNSHIP 19-S RANGE 38-E N.M.P.M.		10. Field and Pool, or Wildcat Hobbs GSA	
11. Elevation (Show whether DF, RT, GR, etc.) 3609.6' GL		12. County Lea	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a total depth of 4486'. On 10-14-83, ran 5-1/2" 15.5# K-55 casing and set at 4486' with DV tool at 3382'. Cemented first stage with 50 bbl POZ-Mix preflush and 385 sx class H Neat. Dropped bomb and shifted DV tool. Circulated out 140 sx of cement. Cemented second stage with 900 sx class H neat and tailed-in with 450 sx class H with 2% CaCl2. Circulated out 420 sx of cement. Rig released 2:00 am, 10-15-83. Drill out and pressure test will be performed by completion unit.

O+4-NMOCD, H 1-HOU, R. E. Ogden, Rm 21.150 1-F. J. Nash, HOU Rm 4.206 1-CMH 1-Texaco
1-Shell 1-Sun 1-Petro Lewis

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles M. Herring TITLE Administrative Analyst DATE 10-18-83

ORIGINAL SIGNED BY JERRY BERTON

OCT 20 1983

APPROVED BY DISTRICT 1 SUPERVISOR TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: