

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
Rustler 892	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Anhydrite 2368	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
T. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2546	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2651	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T. Maguita 964
T. Blinberry	T. Gr. Wash	T. Morrison	T. Culebra 1128
T. Tubb	T. Granite	T. Todilto	T. Salado 1250
T. Drinkard	T. Delaware Sand	T. Entrada	T. Cashile 2326
T. Abo	T. Bone Springs	T. Wingate	T. Ocochillo 2430
T. Wolfcamp	T. Chinle 295	T. Chinle	T.
T. Penn.	T. Santa Fosa 330	T. Permian	T.
T. Cisco (Bough C)	T. Tecovas 414	T. Penn. "A"	T.
	Dewey Lake 556		

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.
No. 2, from.....to.....feet.
No. 3, from.....to.....feet.
No. 4, from.....to.....feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	146	146	Redbeds, Surface				
146	940	794	Anhydrite				
940	1856	916	Anhydrite, Salt				
1856	2272	416	Salt				
2272	2662	390	Anhydrite, Lime				
2662	2755	93	Dolomite, Lime				

RECEIVED

MAY 21 1984

O.C.D.
HOBBS OFFICE