

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501Form C-103
Revised 10-1-79

COPIES RECEIVED	
DISTRIBUTION	
DATE/FILE	
FILE	
REG. S.	
LAND OFFICE	
OPER. LOG	

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. V-188

SUNDARY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REFINER OR PLUG BACK TO A DIFFERENT RESERVOIR.
(SEE REGULATION FOR PERMIT - C-103) FOR SUCH PROPOSALS.)OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well:

UNIT LETTER 0 990 FEET FROM THE South LINE AND 2310 FEET FROM
THE East LINE, SECTION 16 TOWNSHIP 20S RANGE 32E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)

3512' GR

10. Field and Pool, or Wildcat
Halfway Yates

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐REMEDIAL WORK ☐ALTERING CASING ☐TEMPORARILY ABANDON ☐COMMENCE DRILLING OPNS. ☒PLUG AND ABANDONMENT ☐OIL OR ALTER CASING ☐CHANGE PLANS ☐CASING TEST AND CEMENT JOB ☒OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole 9:45 AM 1-1-85. Ran 7 jts of 13-3/8" 68# J-55 casing set 276'. 1-Texas Pattern notched guide shoe set 276'. Insert float set 234'. Cement w/280 sacks Class C 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 1:45 AM 1-2-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 25 sacks. WOC. Drilled out 1:45 PM 1-2-84. WOC 12 hrs. Nippled up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

Ran 23 jts of 8-5/8" 24# J-55 casing set at 940'. 1-Texas Pattern notched guide shoe set at 940'. Insert float at 899'. Cemented w/300 sacks Class C and 1/4#/sack flocele. Tailed in w/300 sacks Class C 2% CaCl2. PD 5:30 PM 1-3-84. Circulated 35 sacks to pit. Drilled out 11:30 AM 1-4-84. WOC 18 hours. Nippled up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry SextonTITLE Production SupervisorDATE 1-5-84ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

APPROVED BY

TITLE

DATE

JAN 9 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JAN 9 1984

HOECS OFFICE