

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-77

1a. Indicate Type of Lease  
State ☐ Free ☒  
3. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name Selby
3. Address of Operator P. O. Box 68 Hobbs, NM 88240	9. Well No. 1
4. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 1 TOWNSHIP 20-S RANGE 35-E N.M.P.M.	10. Field and Pool, or Wildcat Wildcat Bone Springs
15. Elevation (Show whether DF, RT, GR, etc.) 3654.9' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in and rigged up MGF #11. The subject well was spud 7:00 a.m. 2-16-84 with a 17.5" bit. Drilled to a total depth of 394'. On 2-16-84 ran 13-3/8" 54.5# K-55 casing. Casing set at 394'. Cemented with 450 sks Class C cement with 2% CaCl. Circulated out 140 sks cement. WOC 18 hrs. Pressure tested casing 600 lbs for 30 min. Held OK. Reduced bit to 11" and resumed drilling.

0+5-NMOCD, Hobbs 1-R. E. Ogden, Houston-21.150 1-F. J. Nash, Houston-4.206 1-GCC

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mary C. Clark TITLE Asst. Admin. Analyst DATE 2-23-84  
ORIGINAL SIGNED BY JERRY SEXTON  
APPROVED BY DISTRICT 1 SUPERVISOR TITLE \_\_\_\_\_ DATE FEB 27 1984  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
FEB 21 1984  
O.C.D.  
HARRIS OFFICE