

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-2656

SUNDARY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator AMOCO PRODUCTION COMPANY	8. Farm or Lease Name <i>South Hobbs (GSA) Unit</i>
3. Address of Operator P.O. BOX 68 HOBBS, NEW MEXICO 88240	9. Well No. <i>194</i>
4. Location of Well UNIT LETTER <i>0</i> <i>330</i> FEET FROM THE <i>South</i> LINE AND <i>2310</i> FEET FROM THE <i>East</i> LINE, SECTION <i>5</i> TOWNSHIP <i>19-S</i> RANGE <i>38-E</i> NMPM.	10. Field and Pool, or Wildcat <i>Hobbs GSA</i>
11. Elevation (Show whether DF, RT, GR, etc.) <i>3613.9' GR</i>	12. County <i>Lea</i>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☒	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to squeeze, reperforate, and acidize as follows:
MISU and POH with production equipment. RIH with cement retainer and set at 3930'. Cement squeeze with 100sx class C neat and 50sx class C with 4#/sx Tuff-Plug. Reverse out excess cement and WOC. Drill out cement and retainer to 4100'. Pressure test to 1000 psi. Drill out to 4180' and test to 1000 psi. Perforate 3990'-4051', 4142-4150' and 4160-4164' with 2 SSPF. RIH with pin point injection packer spaced to 2 ft. intervals. Acidize 4006-16', 4030-36', 4044-48', 4146-50', and 4160-4164' with 75 gals 15% NE HCl per setting. POH with packer and re-run production equipment. Place well on production.

0+5 AMOCO, H 1-JLB 1-FJN 1-CMH

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Charles M. Herrington* TITLE Administrative Analyst (SG) DATE *10/24/85*

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT SUPERVISOR

APPROVED BY *[Signature]* TITLE *[Signature]* DATE *10/24/85*

CONDITIONS OF APPROVAL, IF ANY:

OCT 28 1985

RECEIVED

OCT 25 1985

U.S. DEPT. OF JUSTICE
HONORARY