

Form 9-331

(May 1963)

UNITED STATES

SUBMIT IN TRIPLICATE*

DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)
GEOLOGICAL SURVEY

Form approved.

BUDGET BUREAU No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.
NM-56264

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1. OIL GAS
WELL ☐ WELL ☐ OTHER Dry hole

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR
Read & Stevens, Inc.8. FARM OR LEASE NAME
NORTH LEA FEDERAL3. ADDRESS OF OPERATOR
P.O. Box 1518, Roswell, NM 88201

9. WELL NO.

1

4. LOCATION OF WELL (Report location clearly and in accordance with State requirements.* See also space 17 below.)
At surface10. FIELD AND POOL, OR WILDCAT
North Lea Devonian1980' FSL and 660' FEL11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA
Sec. 10-20S-34E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3637.5' GL12. COUNTY OR PARISH
Lea13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☒
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Preparations are being made to abandon this hole and skid the rig to re-drill the hole. The hole was not successfully whipstocked as the bit entered the old hole & started drilg on the fish @ 3813'.

RU unit, run 2 3/8" tbg, pump 227sx Class "C" cmt containing .2% CFR-2, .2% Halad-9, circ cmt to sfc, spot 7sx cmt @ sfc, Install dry hole marker. Fill 4 1/2" csg from TD to sfc w/cmt. Plugging procedure approved by Armando Lopez & Bob Pitschkie.

I hereby certify that the foregoing is true and correct

SIGNED

Bruce StuberTITLE Drilling & Production ManagerDATE 3-11-85

(This space for Federal or State office use)

APPROVED BY

Orig. Sgd.

TITLE

DATE

3-22-85

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side