

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator <i>Amoco Production Company</i>	8. Farm Lease Name <i>South Hobbs (GSA) Unit</i>
3. Address of Operator <i>P.O. Box 68, Hobbs NM 88240</i>	9. Well No. <i>185</i>
4. Location of well UNIT LETTER <i>FH</i> <i>2564</i> FEET FROM THE <i>North</i> LINE AND <i>1200</i> FEET FROM THE <i>East</i> LINE, SECTION <i>5</i> TOWNSHIP <i>19-S</i> RANGE <i>38-E</i> NMPM.	10. Field and Pool, or Wildcat <i>Hobbs GSA</i>
15. Elevation (Show whether DF, RT, GR, etc.) <i>3613.4' GR</i>	12. County <i>Dea</i>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 1-5-85 and drilled 39' starting hole. Set 39' of 14", 36.71# conductor. Cemented with 4 1/2 yds Redi-mix. Cactus rig #67 moved in and began continuous drilling operations 1-8-85 with a 12 1/4" bit. Drilled to TD of 1498' and on 1-10-85 set 8 5/8", 24#, K-55 csg. Csg set at 1498' and cemented with 875 sxs class C' w/add. Plug down 3:00 A.M. 1-10-85. Did not circ cmt. Tcmt by temp survey was 110' from surface. RTH with 1" drill pipe to 110' and pumped 106 sxs class C' neat, circulated 8 sxs to pit. Tested casing to 1500psi, tested OK. Reduced bit to 7 7/8" and resumed drilling.
145 NMOC, H 1-JRB 1-FJN 1-GCC 1-Tex 1-Sun 1-Shell 1-PL 2-Areo.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Mary C. Clark* TITLE *Asst. Admin. Analyst* DATE *1-14-85*

APPROVED BY *ORIGINAL SIGNED BY JERRY SEXTON* DISTRICT 1 SUPERVISOR TITLE DATE *JAN 16 1985*
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JAN 15 1985

REC'D
HOBBS OFFICE