Form 3160-5 (November 1983) (Formerly 9-331)	L ED STATES DEPARTMENT OF THE D BUREAU OF LAND MAN	S <sup>H.</sup> <sup>11</sup> SUBMIT INFERIOR (Other VAGEMENT Verse s	IN TRIPLICATE * instructions on re- ide)	Budget Bur Expires Au 5. LEASE DESIGNATI NM-06570	reau No. 1004-0135 Igust 31, 1985 ON AND SERIAL NO.
<u>a different reservo</u>	SUNDRY NOTICES AND REPO orm for proposals to drill ir. Use "APPLICATION FOR F	or to deepen or	plug back to h proposals.)	6. IF INDIAN, ALLO	TTEE OR TRIBE NAME
1. OIL GAS WELL WELL X OTHER				7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Read & Stevens, Inc.				8. FARM OR LEASE NAME Laurie "D" Federal	
3. ADDRESS OF OPERATOR P.O. Box 1518, Roswell, NM 88201				9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with State requirements. * See also space 17 below.)				10. FIELD AND POOL, OR WILDCAT Lea Penn Underig MarMore	
At surface 660'FNL & 990'FEL				11.SEC, T,R,M,OR BLK & SURVEY OR AREA Sec. 15-T20S-R34E	
14. PERMIT NO.		S(Show whether 1 42' GL	DF,RT,GR,etc.)	12. COUNTY OR PARIS	SH 13. STATE
16. C	heck Appropriate Box To In				NM
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	ING WATER SHUT-OFF FRACTURE TREATMENT ALTERING WELL SHOOTING OR ACIDIZING ARANDONMENT * (Other) Install pumping equipment X (NOTE:Report results of multiple completion on Well Completion or Recompletion Report and Log form.)				
I7.DESCRIBE PROPOSED OR COMPLETED OPERATIONS(Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *					
3-18-86 Plld BHP bombs, opnd up on 25/64" chk @ 11:00am, TP 1700psi, oil to surf in 15mins, left flwg over- nite, @ 6:00am 3-18-86 flwg on 25/64" chk @ 50psi, rec'd 40 RO, 41 RW. Prep to install pmpg equip.					
3-19-86 Ld tbg w/37 BBLS 2% KCL wtr, unseat pkr @ 8854', LD 290jts 2 3/8" N-80 tbg, PU bull plug, 1jt as mud anchor 31', perf sub 4', SN 1', 18jts 2 7/8" N-80 533.89', 1.50' tbg anchor 2 7/8"x7", 309jts 2 7/8" N-80 tbg 9114.02', ttl 9685.41', 16' KB, tbg @ 9701.41', SN @ 9665.41', tbg anchor @ 9130.02', SION, PRTD 10,030', Bone Springs perfs 9315'-9871'.					
3-20-86 PU RHBM pmp #T5-676 21/2"x11/2"x16'x18'x21', chrome barrel, spray metal plunger, 157" stroke, ran 204jts 3/4" rds,122jts 7/8" rds, 58jts 1" rds, 22' polish rd, strtd pmpg @ 5:00pm, @ 6:00am eng died.					
I hereby certify that t SIGNED	he foregoing is true and c		ng & Production Mana	iger DATE Ma	arch 20, 1986
(This space for Federa APPROVED BY CONDITIONS OF APPROVAL	al or State office use)	TIRE		DATE	
, CC	CORTED FOR RECORD				
	LWD MAR 2 5 1986				

CAPIEBAD, NEW MEXICO