

Expires August 31, 1985

HOBBS, NEW MEXICO 88240

5. LEASE DESIGNATION AND SERIAL NO.
NM-06570

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to
a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1. OIL GAS
WELL ☐ WELL ☒ OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR
Read & Stevens, Inc.

8. FARM OR LEASE NAME
Laurie "D" Federal

3. ADDRESS OF OPERATOR
P.O. Box 1518, Roswell, NM 88201

9. WELL NO.

4. LOCATION OF WELL (Report location clearly and in accordance with State
requirements. * See also space 17 below.)

10. FIELD AND POOL, OR WILDCAT
Lea Penn

At surface
660' FNL & 990' FEL

11. SEC, T, R, M, OR BLK & SURVEY OR AREA
Sec. 15-T20S-R34E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3642' GL

12. COUNTY OR PARISH
Lea

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON * ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT * ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) BHP test results & set psi plug ☒

(Other) ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including
estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured
and true vertical depths for all markers and zones pertinent to this work.) *

1-24-86 TP 2417psi DW.
1st flow 2273psi 4/64"chk 231.3 MCF
2nd flow 2160psi 5/64"chk 358.1 MCF
3rd flow 2018psi 7.25/64"chk 581.3 MCF
4th flow 1772psi 11/64"chk 937.3 MCF
Prod 6 BO dur 4hr tst, left flwg overnight, @ 6:00am 1-24-86 1600psi, 11/64"chk, 697 MCF, 23 BO

1-25-86 6:00am flwg, 1500psi, 12/64" chk, 180psi, 17" dflr, 60°F, 763 MCF, 49 BO. Prep to set psi plug.

1-26-86 1450psi, 12/64" chk, 768 MCF, 15 BO, 3 1/2 hrs. RU Bennett WL, set FSG Baker plug in F-nipple,
1.875" @ 12,930', bld dwn, 1d tbg w/49.7 BBLS 2% KCL wtr, SITP 500psi, bld off press. SION.

1-27-86 TP 2400psi, bld dwn.

I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling & Production Manager

DATE January 27, 1986

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AWD
JAN 30 1986

CARLSBAD, NEW MEXICO

RECEIVED

JAN 28 1986

HOBBS, NEW MEXICO

RECEIVED

FEB - 3 1966

U.S. AIR FORCE