

LEASE DESIGNATION AND SERIAL NO  
NM-06570

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir Use "APPLICATION FOR PERMIT-" for such proposals )

1 OIL ☐ GAS ☐  
WELL ☐ WELL ☒ OTHER \_\_\_\_\_

2 NAME OF OPERATOR  
Read & Stevens, Inc

3 ADDRESS OF OPERATOR  
P O Box 1518, Roswell, NM 88201

4 LOCATION OF WELL (Report location clearly and in accordance with State requirements \* See also space 17 below )  
At surface  
660' NL & 990' FEL

6 IF INDIAN, ALLOTTEE OR TRIBE NAME  
-

7 UNIT AGREEMENT NAME  
-

8 FARM OR LEASE NAME  
Laurie "D" Federal

9 WELL NO  
1

10 FIELD AND POOL, OR WILDCAT  
Lea Penn

11 SEC T, R, M, OR BLK AND  
SURVEY OR AREA  
Sec 15-T20S-R34E

14 PERMIT NO  
-

15 ELEVATIONS (Show whether DF, RT, GR, etc )  
3642' GL

12 COUNTY OR PARISH  
Lea

13 STATE  
NM

16 Check Appropriate Box To Indicate Nature of Notice, Report, Other Data

NOTICE OF INTENTION TO

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐  
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐  
SHOOT OR ACIDIZE ☐ ABANDON\* ☐  
REPAIR WELL ☐ CHANGE PLANS ☐  
(Other) ☐

SUBSEQUENT REPORT OF

WATER SHUT-OFF ☐ REPAIRING WELL ☐  
FRACTURE TREATMENT ☐ ALTERING CASING ☐  
SHOOTING OR ACIDIZING ☐ ABANDONMENT\* ☐  
(Other) Spud & Cement Casing ☒  
(NOTE Report results of multiple completion on Well Completion or Recompletion Report and Log form )

17 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work )\*

9-14-85 Spudded a 26" hole @ 4 30 A M 9-14-85

9-15-85 T D 26" hole @ 12 00 midnight 9-14-85, @ 520'

9-16-85 Ran 15 jts , total 502', 20" 94#/ft , K-55, St&c and Buttress, set @ 520', float collar @ 468', cement w/500 sx HLW cement w/1/4#/sx flocele, 2% CaCl<sub>2</sub>, tailin w/200 sx Class "C" w/1/4#/sx flocele, 2% CaCl<sub>2</sub>; plug down @ 11 00 A M , 9-15-85, circulated 239 sx

9-17-85 WOC 19 hrs, test casing @ 800 psi for 30 min, tested satisfactorily

ACCEPTED FOR RECORD

OCT 21 1985

RECEIVED

OCT 15 1985

HOBBS, NEW MEXICO

I hereby certify that the foregoing is true and correct

SIGNED

*B. Stobbs*

TITLE Drilling & Production Manager

DATE September 17, 1985

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY