

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐	GAS WELL ☐	OTHER- Water injection	7. Unit Agreement Name
Name of Operator AMOCO PRODUCTION COMPANY			8. Farm or Lease Name South Hobbs (GSA) Unit
Address of Operator P. O. Box 68, Hobbs, NM 88240			9. Well No. 207
Location of Well UNIT LETTER <u>L</u> , <u>1944</u> FEET FROM THE <u>South</u> LINE AND <u>624</u> FEET FROM THE <u>West</u> LINE, SECTION <u>5</u> TOWNSHIP <u>19-S</u> RANGE <u>38-E</u> N.M.P.M.			10. Field and Pool, or wildcat Hobbs GSA
15. Elevation (Show whether DF, RT, GR, etc.) 3619.5 GR			12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☒	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MI and RUSU 1-29-87. Install BOP. Release packer and POH tubing and packer. Dump 7 sx sand down casing. Run collar locator. Tag sand 4226. Run 3-1/2" bailer and dump Calseal. Tag calseal 4218. Run 3-1/2" bailer dump Calseal. Tag Calseal 4214. Run 3-1/2" casing gun. Perf 4138-50. 4 JSPF. RIH 5-1/2" Howco PPI packer, 2-3/8" seating nipple. Packer set at 4088. Test to 1000# and OK. Drop RFC valve and acidize 4138-4210. 140 gals 15% NE HCL per two ft setting. Flush 29 BW and max pressure 3000#. Release packer and fish RFC valve. Flush casing and 100 BW. RIH 5-1/2" UNI VI with packer set at 4077. Test packer to 500#. RD and MOSU 2-3-87.

IPWO: 548 BWPD and TP 100#.
IAWO: 980 BWPD and TP Vac.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

by S. Brownlee TITLE Administrative Analyst DATE 2-11-87

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

APPROVED BY JERRY SEXTON TITLE DISTRICT 1 SUPERVISOR DATE FEB 16 1987

CONDITIONS OF APPROVAL, IF ANY: