(2002)	UNIT STATES SUBMIT IN TRI	ns on re Budget Bureau No. 42-R1424.
DEPARTMENT OF THE INTERIOR (Other Instructions GEOLOGICAL SURVEY		5. LEASE DESIGNATION AND BERIAL NO. NM-56264
SUNDRY NOT (Do not use this form for propor Use "APPLICA	ICES AND REPORTS ON WELLS sals to drill or to deepen or plug back to a different reservition FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME voir.
1. OIL GAS WELL OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR		8. FABM OR LEASE NAME
Read & Stevens, Inc. 3. ADDRESS OF OPERATOR		North Lea Federal 9. WELL NO.
P. O. Box 1518, Roswel	1, New Mexico 88201 learly and in accordance with any State requirements.*	2
At surface	early and in accordance with any State requirements."	10. FIELD AND POOL, OR WILDCAT
1980' FWL & 1880' FNL		Mildcat 11. SEC., T., B., M., OR BLK, AND SURVEY OR AREA
		Sec. 10, T-20-S, R-34E
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3639 GL	12. COUNTY OB PARISH 13. STATE Lea NM
16. Check Ap	propriate Box To Indicate Nature of Notice, Re	
NOTICE OF INTER		BUBSEQUENT REPORT OF :
TEST WATER SHUT-OFF	ULL OR ALTER CASING WATER SHUT-OFF	REPAIRING WELL
	IULTIPLE COMPLETE FRACTURE TREAT	
	BANDON* SHOOTING OR ACI	MARLETION
()ther)	(Note: Reg	port results of multiple completion on Well or Recompletion Report and Log form.)
new 2-3/8", N-80, El bit, 6 3-1/2" drill co Gontinued going in hole Drilled cement and DV 4-Sep Continued going in hole Pulled out of hole; add tool several time. Con 9-Sep Pulled out of hole; laid 7-Sep Went in hole with Vanr sealing connector and set packer at 13,158. 13,178 13,188 13,193 Rigged-down BOP and 1	up pulling and reverse units. Unloaded, racked and f U, S rd., 4.7 */ft. tubing with AB modified couplin ollars and went in hole with same. A with drill string to 10,123' KB; tagged cement at tool. Circulated hole clean. A tool. Circulated hole clean. A tools of KB; closed BOP, pressure tested with ed casing scraper to string. Went in hole to DV too tinued going in hole to 13,636' KB. Circulated hole down bit, scraper and drill collars. A tubing conveyed perforating system, packer asse tubing. Ran Welex correlation log and adjusted dep 79' KB, "on-off" tool at 13,155.54' KB. Guns set to 13,182' KB to 13,216' KB. hippled-up well head. Dropped bar to perforate at 3 install test equipment.	gs. Picked-up 4-1/2" that point. 1500 psig, held OK. i; worked through DV with 398 KCL water. mbly, "on-off" ths. Spaced out and to perforate as follows:
18. I hereby ferding that the foregoing is SIGNED Udmes F / 0 Briant	and TITLE Agent for Read &	Stevens, IDETE 2/9/87
(This space for Federal or State office		ACCEPTED FOR RECORD
APPROVED BY CONDITIONS OF APPROVAL, IF AN	TITLE Y :	DATE
		SEP 1 6.1987

\*See Instructions on Reverse Side

.

SJS CARLSBAD DEW MEXICO