

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(Other Districts may use 10
version added)

Budget Bureau No. 1004--011
Expires August 31, 1985
LEASE DESIGNATION AND SERIAL NO.

NM-51844

INDIAN, ALLOTTEE OR TRIBE NAME

UNIT AGREEMENT NAME

FARM OR LEASE NAME

Federal

WELL NO.

3

FIELD AND POOL OR WILDCAT

West Teas SR (Yates)

SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 9, T20S, R33E

COUNTY OR PARISH 13. STATE

Lea

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR
Grover-McKinney Oil Company
3. ADDRESS OF OPERATOR
P O Box 3666, Midland, Texas 79702
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below)
At surface

1980' FSL & 2310' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RL, GR, etc.)

3542.9' GR

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

SUBSEQUENT REPORT OF:

TEST WATER SHUT OFF

PULL OR ALTER CASING

ALTER WELL DEPTH

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

TRAP OR TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

REPAIR OR ACIDIZE

ABANDONMENT*

REPAIR WELL

CHANGE PLUG

Surface & Production Casing ☒

(Other)

(Note: Report results of multiple completion on Well
Completion or Recore Completion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (If well is directionally drilled, give subsurface locations and bearings and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well at 1:30 pm 2/26/88.

2/28/88 Ran 29 jts (1205' overall) 8 5/8" 24# J-55 ST&C casing. Cemented at 1218' w/500 sx Halliburton Lite 1/4# flocele & 250 sx Premium Plus 2% Calcium Chloride. Circulated 213 sx. Plug down @ 5:45 am 2/28/88.

3/4/88 Ran 80 jts (3422.78' overall) 4 1/2" 10.5# J-55 casing. Cemented @ 3420' w/450 sx Halliburton Lite 15# salt 1/4# flocele 5# gilsonite & 200 sx Premium Plus 2% Calcium Chloride. Top of cement 600'. Plug down @ 5 pm 3/4/88.

RECEIVED
MAR 16 11 02 AM '88
CARLSBAD RESOURCE
AREA HEADQUARTERS

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

March 9, 1988

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

SJS