## State of New Mexico Energy, humerals and Natural Resources Department

Form C-103 Revised 1-1-89

S. Indicate Type of Lease   STATE     FEE	DISTRICT I P.O. Box 1990, Hobbs, NM 88240 DISTRICT II	OIL CONSERVATION DIVISION P.O. Box 2088		WELL API NO. 30-025-30332	
DISTRICT MA, ALIAC, NM. 87410  Sunday Notices and Reports on Wells  (DO NOT Use this form for proposals to delil or to deepen of Plus back to a 1-1543-1  (DO NOT Use this form for proposals to delil or to deepen of Plus back to a Deference of Plus Back to a NORTH MONUMENT G/SA  1. Type of Well:  "WILL []	P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico	87504-2088		
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUS BACK TO A  DEFERENT RESERVOR. USE APPLICATION FOR PERMAT'  (PORM C-101) FOR SUCH PROPOSALS.  1. Type of Well.  OTHER  AMERICA  AMERICA	DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410			STATE FEE	
TOWN USE THIS FORM FOR PROPAGALS TO DRILL ON TO DEEPEN OR PLUG BACK TO A DEFFERENT RESERVOIR USE "APPLICATION FOR PEMAT"    Type of Wall:	CUNDDY NOTE	OFO AND DEPONTS ON ME			
AMERADA HESS CORPORATION  1. Madras of Operator  MERADA HESS CORPORATION  1. Address of Operator  DRAWER DA MONUMENT, NM 88265  2. Wash No.  1. Address of Operator  DRAWER DA, MONUMENT, NM 88265  2. Well Location  Duit Leaser P : 760 Peet From The EAST Lise and 610 Feet From The SOUTH Lise Section  19 Township 19S Range 37E NAGPM LEA  County  10. Elevation (Notworkship DP, RRB, RT, GR, acc)  11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING  TEMPORABLY ABANDON CHANGE PLANS  CHANGE PLANS  COMMENCE DRILLING OPNS. PLUG AND ABANDONIMENT OF THE TESTED CASING  OTHER:  1. Describe Proposed or Completed Operations (Cherry state all perinent dessils, and give pertinent desses, including estimated date of starting any proposed word) uses RULL HIGS.  5-21 THRU 5-26-93  MIRU X-PERT WELL SER. PULL ING UNIT. REMOVED 6" 900 TUBING HEAD FLANGE & INSTALLED A 6" 900 MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TITH WITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TITH WITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TITH WITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TITH WITH 4-3-1/4" DRILL BIT, TAGGED AT 3,747' & MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TITH WITH 4-3-1/4" DRILL BIT, TAGGED AT 3,747' & MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TITH WITH 4-3-1/4" DRILL BIT, TAGGED AT 3,747' & MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TITH WITH 4-3-1/4" BAKER MODEL RESED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & 6" 900 X AND X 11" 3M X	( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"				
AMERADA HESS CORPORATION  Addressed Operator  DRAWER D, MONUMENT, NM 88265  **Well Locations  Usit Letter P: 760 Feet From The EAST Line and 610 Foet From The SOUTH Line Section 19 Township 19S Range 37E NAMPM LEA COCKING  Section 19 Township 19S Range 37E NAMPM LEA COCKING  NOTICE OF INTENTION TO:  Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  REMEDIAL WORK ALTERING CASING CHANGE PLANS CASING TEST AND CEMENT JOBS  CASING TEST AND CEMENT JOBS  TEMPORABILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONIMENT COMMENCE DRILLING OPNS.  PULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS.  12. Describe Proposed or Completed Operations (Clearly state all persioned details, and give persioned data, including estimated data of starting any proposed world SEE RULE 1103.  THRU X-PERT WELL SER. PULL ING UNIT. REMOVED 6" 900 TUBING HEAD FLANGE & INSTALLED A 6" 900 MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TIH MITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. TIH MITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TIH MITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. TIH MITH A 5-1/2" REDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. THE MITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. TIH MITH A 5-1/2" REDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. THE MITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. THE MITH A 5-1/2" REPORT AND A STARLED PACKING TO 2000 PSI. INSTANLED PACKING AND 7-1/16" 3M X X 11" 3M AND X 11" 3M	MET   MET	OTHER		·	
DRAWER D, MONUMENT, NM 88265  19					
DRAWER D, MONUMENT, NM 88265  4. Well Lession  Unit Letter P: 760 Feet From The EAST  Line and 610 Feet From The SOUTH Line  Socion 19 Township 19S Range 37E NAUTM LEA  Township 19S Range 37E NAUTM LEA  County  10. Elevation (Show whather DP, RKB, RT, CR. etc.)  11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS  COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT  TEMPORABLY ABANDON CHANGE PLANS  CASING TEST AND CEMENT JOB  OTHER: ISTED CASING  OTHER: ISSTED CASING  OT					
Section 19 Township 19S Range 37E NORTH LEA COUNTY    10. Elevation (Show whather DF, RKB, RT, GR, etc.)   11.   Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO:   SUBSEQUENT REPORT OF:	DRAWER D, MONUMENT, NM	88265	·	1	
10. Elevation (Show whether DF, RKB, RT, CR, etc.)   11.   12.   12.   12.   12.   12.   13.   14.		Feet From TheEAST	Line and61	O Feet From The SOUTH Line	
THE WITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC, CASING WATER THE WITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC, CASING TO 535 PSI IN 30 MIN. CHECKED SUFFACE-PRODUCTION CASING ANNULUS & PRESS. DECREASED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & F1-1/2" CASING TINSTALLED A 7900 MANUAL BOP & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" CASING TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & F1-1/2" CASING TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TILB WITH BAKER MODEL R DOUBLE GRIP PKR. REMOVED BAYER MODEL R DOUBLE GRIP PKR. REMOVED BAYER MODEL R DOUBL	Section 19		nge 37E	NMPM LEA COUNTY	
SUBSEQUENT REPORT OF:  PERFORM REMEDIAL WORK  PLUG AND ABANDON  CHANGE PLANS  COMMENCE DRILLING OPNS. PLUG AND ABANDON PULL OR ALTER CASING  OTHER: TESTED CASING  COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT  OTHER: TESTED CASING  OTHER: TESTED CASING  THERE TESTED CASING  THE WITH A 57.4" REMOVED 6" 900 TUBING HEAD FLANGE & INSTALLED A 6" 900 MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. THE WITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. TIH WITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING W/100 BBLS. FRESH WATER. PRESS. TESTED CSG. FR. 0' TO 3,640'. PRESS. DECREASED FR. 545 PSI TO 335 PSI IN 30 MIN. CHECKED SURFACE-PRODUCTION CASING ANNULUS & FOUND 25 PSI. OPENED ANNULUS & PRESS. DECREASED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & 6" 900 X 10" 900 TUBING SPOOL. DRESSED OFF 5-1/2" CASING STUB. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TIH W/ GRIP PKR. REMOVED 6" 900 MANUAL BOP & TOH W/5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TOH WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TOH W/5-1/2" BAKER MODEL R DOUBLE SUPY. ADMIN. SER.  TITLE SUPY. ADMIN. SER.  TITLE SUPY. ADMIN. SER.  TITLE SUPY. ADMIN. SER.  TITLE SUPY. ADMIN. SER.  THE SUPY. AD		10. Elevation (Show whether	DF, RKB, RT, GR, etc.)		
SUBSEQUENT REPORT OF:  PERFORM REMEDIAL WORK  PLUG AND ABANDON  CHANGE PLANS  COMMENCE DRILLING OPNS. PLUG AND ABANDON PULL OR ALTER CASING  OTHER: TESTED CASING  COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT  OTHER: TESTED CASING  OTHER: TESTED CASING  THERE TESTED CASING  THE WITH A 57.4" REMOVED 6" 900 TUBING HEAD FLANGE & INSTALLED A 6" 900 MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. THE WITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. TIH WITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING W/100 BBLS. FRESH WATER. PRESS. TESTED CSG. FR. 0' TO 3,640'. PRESS. DECREASED FR. 545 PSI TO 335 PSI IN 30 MIN. CHECKED SURFACE-PRODUCTION CASING ANNULUS & FOUND 25 PSI. OPENED ANNULUS & PRESS. DECREASED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & 6" 900 X 10" 900 TUBING SPOOL. DRESSED OFF 5-1/2" CASING STUB. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TIH W/ GRIP PKR. REMOVED 6" 900 MANUAL BOP & TOH W/5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TOH WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & TOH W/5-1/2" BAKER MODEL R DOUBLE SUPY. ADMIN. SER.  TITLE SUPY. ADMIN. SER.  TITLE SUPY. ADMIN. SER.  TITLE SUPY. ADMIN. SER.  TITLE SUPY. ADMIN. SER.  THE SUPY. AD	11. Check Appropriate Box to Indicate Nature of Notice Report of Other Date				
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT THE PULL OR ALTER CASING TEST AND CEMENT JOB!  12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starring any proposed work). SEE RULE 1103.  5-21 THRU 5-26-93  MIRU X-PERT WELL SER. PULLING UNIT. REMOVED 6" 900 TUBING HEAD FLANGE & INSTALLED A 6" 900 MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TIH WITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. TIH WITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING W/100 BBLS. FRESH WATER. PRESS. TESTED CSG. FR. 0' TO 3,640'. PRESS. DECREASED FR. 545 PSI TO 535 PSI IN 30 MIN. CHECKED SURFACE-PRODUCTION CASING ANNULUS & FOUND 25 PSI. OPENED ANNULUS & PRESS. DECREASED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & 6" 900 X 10" 900 TUBING SPOOL. DRESSED OFF 5-1/2" CASING STUB. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TIH W/RETRIEVING TOOL. RELEASED RBP & TOH W/5-1/2" RBP. TOH WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & INSTALLED 7-1/16" 3M TUBINGHEAD FLANGE & SLIP  TITLE  TYPE OR FRIENT NAME  ROY L. WHEELER, JR.  THE STREET NAME TO BE ACT OF THE PACK UND STARLED PACK UND SER.  THE SUPPLY ADMIN. SER.  JUL 16 1993  ATTROVED BY DATE  THE STREET NAME TO STARLED BY ACT OF THE STARLED PACK UND SER.  JUL 16 1993	NOTICE OF INT	ENTION TO:			
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: TESTED CASING  OTHER: TESTED CASING  12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  5-21 THRU 5-26-93  MIRU X-PERT WELL SER. PULLING UNIT. REMOVED 6" 900 TUBING HEAD FLANGE & INSTALLED A 6" 900 MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TIH WITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. TIH WITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING W/100 BBLS. FRESH WATER. PRESS. TESTED CSG. FR. 0" TO 3,640'. PRESS. DECREASED FR. 545 PSI TO 535 PSI IN 30 MIN. CHECKED SURFACE-PRODUCTION CASING ANNUALS & FOUND 25 PSI. OPENED ANNULUS & PRESS. DECREASED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & 6" 900 X 10" 900 TUBING SPOOL. DRESSED OFF 5-1/2" CASING STUB. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TIH W/RETRIEVING TOOL. RELEASED RBP & TOH W/5-1/2" RBP. TOH WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & INSTALLED 7-1/16" 3M TUBINGHEAD FLANGE & SLIP  - (CONT. OVER)  Thereby certify that deplatformation above is thus and complete to the best of my knowledge and ballet.  SUPV. ADMIN. SER.  THE SUPV. ADMIN. SER.  THE SUPV. ADMIN. SER.  THE PRICE NO. 393-2144  THE PRICE NO. 393-2144  THE PRICE NO. 393-2144	PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING	
OTHER:  OTHER: IESTED CASING  I2 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  5-21 THRU 5-26-93  MIRU X-PERT WELL SER. PULLING UNIT. REMOVED 6" 900 TUBING HEAD FLANGE & INSTALLED A 6" 900 MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TIH WITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. TIH WITH A 5-1/2" ELDER LOK-SET RETREVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING W/100 BBLS. FRESH WATER. PRESS. TESTED CSG. FR. 0' TO 3,640'. PRESS. DECREASED FR. 545 PSI TO 535 PSI IN 30 MIN. CHECKED SURFACE-PRODUCTION CASING ANNULUS & FOUND 25 PSI. OPENED ANNULUS & PRESS. DECREASED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & 6" 900 X 10" 900 TUBING SPOOL. DRESSED OFF 5-1/2" CASING STUB. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TIH W/ RETRIEVING TOOL. RELEASED RBP & TOH W/5-1/2" RBP. TOH WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & INSTALLED 7-1/16" 3M TUBINGHEAD FLANGE & SLIP  (CONT. OVER)  Thereby contrib that the information above is true and complete to the boat of any knowledge and bolded.  SUPV. ADMIN. SER.  THE THEREPHONE NO. 393-2144  (Chies space for State Use)  Orig. Signaed by Paul Kautz Geologist  TILL  Geologist  TILL  DATE  THE TABLEPHONE NO. 393-2144	TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING		
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed worth) SEE RULE 1103.  5-21 THRU 5-26-93  MIRU X-PERT WELL SER. PULLING UNIT. REMOVED 6" 900 TUBING HEAD FLANGE & INSTALLED A 6" 900 MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TIH WITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. TIH WITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING W/100 BBLS. FRESH WATER. PRESS. TESTED CSG. FR. 0' TO 3,640'. PRESS. DECREASED FR. 545 PSI TO 535 PSI IN 30 MIN. CHECKED SURFACE-PRODUCTION CASING ANNULUS & FOUND 25 PSI. OPENED ANNULUS & PRESS. DECREASED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & 6" 900 X 10" 900 TUBING SPOOL. DRESSED OFF 5-1/2" CASING STUB. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TIH W/RETRIEVING TOOL. RELEASED RBP & TOH W/5-1/2" RBP. TOH WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & INSTALLED 7-1/16" 3M TUBINGHEAD FLANGE & SLIP (CONT. OVER)  I bereby certify that the information above is true and complete to the best of my knowledge and belief.  SUPV. ADMIN. SER.  THE TYPE OR FRENT HAMBE  ROY L. WHEELER, JR.  THE SUPV. ADMIN. SER.  JUL 16 1993  ATTECRETATION AND AND AND AND AND AND AND AND AND AN	PULL OR ALTER CASING		CASING TEST AND C	EMENT JOEI 🔲 -	
MIRU X-PERT WELL SER. PULLING UNIT. REMOVED 6" 900 TUBING HEAD FLANGE & INSTALLED A 6" 900 MANUAL BOP. TOH W/2-7/8" TBG. & BAKER TAC. TIH WITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. TIH WITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING W/100 BBLS. FRESH WATER. PRESS. TESTED CSG. FR. 0' TO 3,640'. PRESS. DECREASED FR. 545 PSI TO 535 PSI IN 30 MIN. CHECKED SURFACE-PRODUCTION CASING ANNULUS & FOUND 25 PSI. OPENED ANNULUS & PRESS. DECREASED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & 6" 900 X 10" 900 TUBING SPOOL. DRESSED OFF 5-1/2" CASING STUB. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TIH W/RETRIEVING TOOL. RELEASED RBP & TOH W/5-1/2" RBP. TOH WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & INSTALLED 7-1/16" 3M TUBINGHEAD FLANGE & SLIP  (CONT. OVER)  Thereby certify that the information above is true sed complete to the best of my knowledge and belief.  SUPV. ADMIN. SER.  THE SUPV. ADMIN. SER.  THE SUPV. ADMIN. SER.  THE PHOND NO. 393-2144  THE PROVED BY BATE DATE  THE DA	OTHER:				
MIRU X-PERT WELL SER. PULLING UNIT. REMOVED 6" 900 TUBING HEAD FLANGE & INSTALLED A 6" 900 MANUAL BOP. TOH W/Z-7/8" TBG. & BAKER TAC. TIH WITH 4-3/4" DRILL BIT, TAGGED AT 3,747' & TOH. TIH WITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING W/100 BBLS. FRESH WATER. PRESS. TESTED CSG. FR. 0' TO 3,640'. PRESS. DECREASED FR. 545 PSI TO 535 PSI IN 30 MIN. CHECKED SURFACE-PRODUCTION CASING ANNULUS & FOUND 25 PSI. OPENED ANNULUS & PRESS. DECREASED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & 6" 900 X 10" 900 TUBING SPOOL. DRESSED OFF 5-1/2" CASING STUB. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TIH W/RETRIEVING TOOL. RELEASED RBP & TOH W/5-1/2" RBP. TOH WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & INSTALLED 7-1/16" 3M TUBINGHEAD FLANGE & SLIP   (CONT. OVER)  I hereby certify that phosinformation above in true and complete to the best of my knowledge and belief.  SUPV. ADMIN. SER. 7-12-93  TITLE  TITLE  Orig. Sigraed by Paul Kautz Geologist  TITLE  JUL 16 1993  ATTROVED BY DETERMINED.	12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.				
TOH. TIH WITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING W/100 BBLS. FRESH WATER. PRESS. TESTED CSG. FR. 0' TO 3,640'. PRESS. DECREASED FR. 545 PSI TO 535 PSI IN 30 MIN. CHECKED SURFACE-PRODUCTION CASING ANNULUS & FOUND 25 PSI. OPENED ANNULUS & PRESS. DECREASED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & 6" 900 X 10" 900 TUBING SPOOL. DRESSED OFF 5-1/2" CASING STUB. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TIH W/RETRIEVING TOOL. RELEASED RBP & TOH W/5-1/2" RBP. TOH WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & INSTALLED 7-1/16" 3M TUBINGHEAD FLANGE & SLIP  - (CONT. OVER)  Thereby certify that the information above is true and complete to the best of my knowledge and belief.  SUPV. ADMIN. SER.  TITLE  TYPE OR FRINT NAME  Orig. Signed by Paul Kautz  Geologist  TITLE  JUL 16 1993  ATTROVED BY  ATTROVED BY  PAUE  TITLE  JUL 16 1993	5-21 THRU 5-26-93				
I bereby certify that the information above is true and complete to the best of my knowledge and belief.  SUPV. ADMIN. SER.  TITLE  TOTAL OF PRINT NAME  ROY L. WHEELER, JR.  THE PRINT NAME  Orig. Signed by Paul Kautz Geologist  TITLE  JUL 16 1993	TOH. TIH WITH A 5-1/2" ELDER LOK-SET RETRIEVABLE BRIDGE PLUG SET AT 3,640' & CIRC. CASING W/100 BBLS. FRESH WATER. PRESS. TESTED CSG. FR. 0' TO 3,640'. PRESS. DECREASED FR. 545 PSI TO 535 PSI IN 30 MIN. CHECKED SURFACE-PRODUCTION CASING ANNULUS & FOUND 25 PSI. OPENED ANNULUS & PRESS. DECREASED TO 0 PSI INSTANTLY. REMOVED 6" 900 MANUAL BOP & 6" 900 X 10" 900 TUBING SPOOL. DRESSED OFF 5-1/2" CASING STUB. INSTALLED PACKING AND 7-1/16" 3M X 11" 3M NAT'L TUBING SPOOL & TESTED PACKING TO 2000 PSI. INSTALLED 6" 900 MANUAL BOP & TIH W/RETRIEVING TOOL. RELEASED RBP & TOH W/5-1/2" RBP. TOH WITH A 5-1/2" BAKER MODEL R DOUBLE GRIP PKR. REMOVED 6" 900 MANUAL BOP & INSTALLED 7-1/16" 3M TUBINGHEAD FLANGE & SLIP				
SIONATURE SUPV. ADMIN. SER. 7-12-93  TYPE OR FRINT NAME  ROY L. WHEELER, JR.  THLE SUPV. ADMIN. SER. 7-12-93	I hereby cartify that the information above in the			- (CONT. OVER)	
TYPE OR FRINT NAME  ROY L. WHEELER, JR.  THE SPECE FOR SINGE Use)  Orig. Signed by Paul Kautz Geologist  THUE  THE PHONE NO. 393-2144			SUPV. ADMIN.	SER. 7-12-93	
Paul Kautz Geologist TITLE  Unig. Signed by Paul Kautz  Geologist TITLE  DATE	TYPEOR PRINT NAME ROY L. WHI			TELEPHONE NO. 393-2144	
DATE	0	Paul Kautz		1 g 1002	
		Geologist m	u	DATE DATE	

ASSEMBLY. SET PKR. AT 3,643 W/10,000# COMPRESSION. RIGGED UP SWABBING EQUIPMENT & SWABBED WELL. LOADED CASING-TUBING ANNULUS W/65 BBLS. PKR. FLUID. RIGGED DOWN PULLING UNIT, CLEANED LOCATION & RESUMED FLOWING WELL ON A 10/64" CHOKE. TEST OF 7-1-93: PROD. 1 B.O., 0 B.W., & 23 MCFGPD IN 24 HRS.