

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☒ Fee ☐  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Chevron U.S.A. Inc. 3. Address of Operator P.O. Box 670, Hobbs, NM 88240 4. Location of Well UNIT LETTER <u>P</u> <u>760</u> FEET FROM THE <u>East</u> LINE AND <u>610</u> FEET FROM THE <u>South</u> LINE, SECTION <u>19</u> TOWNSHIP <u>19S</u> RANGE <u>37E</u> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3660'	7. Unit Agreement Name 8. Farm or Lease Name Graham State NCT-D 9. Well No. 3 10. Field and Pool, or WHdcat Eunice Monument GB/S. 12. County Lea
--	--

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drig 7 7/8" hole at 10:00PM 5-5-88. TD 7 7/8" hole at 6:30AM 5-9-88.  
Circ f/logs. Run CNL-ZDL and DLL-MLL. Ran 5 1/2", K-55, LT&C, 8rd csg  
to 3978' w/ FC at 3896'. Circ. casing capacity. Cmt w/550sx Cl C, Tail  
w/ 275sx Cl C. Displaced w/ FW. Bump plug w/2000psi, at 9AM 5-10-88.  
Floats held, circ 162 sx to surf. ND BOPE, cut off 5 1/2" csg, install  
tbq spool. Test void to 2800psi, ok. Release rig at 2PM 5-10-88.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED M. E. Ahern TITLE Staff Drilling Engineer DATE May 17, 1988

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISCLAIMER DATE 5-17-88  
CONDITIONS OF APPROVAL, IF ANY: