

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
NEW MEXICO

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ON WELL WELL OTHER APR 11 8 35 AM '88

2. NAME OF OPERATOR National Coop. Refinery Assoc.

3. ADDRESS OF OPERATOR 415 W. Wall, Suite 2215, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
1890'
1980' FSL, 660' FWL of Section 11

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3636.5' GL

5. LEASE DESIGNATION AND SERIAL NO. NM-0361-0631
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Federal 11-20-34
9. WELL NO. 3
10. FIELD AND POOL, OR WILDCAT Lea Penn
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 11, T-20-S, R-34-E
12. COUNTY OR PARISH Lea 13. STATE New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other) Spud Date & Casing Setting

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud Date: 4-07-88 @ 10:15 AM

CONFIDENTIAL REPORT

Hole Size: 17 1/2"

Casing: Guide Shoe & Insert Float, 453.54' (10 Jts) 13 3/8" J-55 54.5# ST&C and 444.90' (11 Jts) 13 3/8" H-40 48# ST&C Casing set @ 876'. 5 Centralizers.

Cement: 460 sx Class C 2% CaCl-2, 4% Gel, 1/4# Flocele, 1.76 Yield, 13.5# per gal and 300 sx Class C 2% CaCl-2, 1.32 Yield, 14.8# per gal.

142 sx cement circulated to surface.

Plug bumped @ 11:00 AM 4-08-88. Tested @ 500 psi, held OK.

Witnessed By: Walter Cox / BLM - Hobbs, New Mexico

18. I hereby certify that the foregoing is true and correct

SIGNED Terrie A. Baye TITLE Production Clerk DATE 4-08-88

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

SJS