

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
SUNDRY NOTICES AND REPORTS ON WELLS  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

Expires August 31, 1985  
5. LEASE DESIGNATION AND SERIAL NO.  
LC-064194  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

BILL FENN, INC.

3. ADDRESS OF OPERATOR

P. O. DRAWER 569, GIDDINGS, TEXAS 78942

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

660' FSL & 660 FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3632' GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

POWELL FEDERAL

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 4-T20S-R34E

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEXICO

10. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANE

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

INTERMEDIATE CASING: SETTING DEPTH WAS CHANGED FROM 4200' TO 5000'. 12 1/4 HOLE WAS DRILLED TO 4780. FROM 4780 TO 5000, 11" HOLE WAS DRILLED.

CEMENTING IN TWO STAGES: 1ST STAGE - 525 SKS. HALLIBURTON LITE WITH 1/4# FLOCELE & 5# GILSONITE - 300 SKS. CLASS C WITH 2% CaCl<sub>2</sub>.

2ND STAGE - 1350 SKS HALLIBURTON LITE WITH 1/4# FLOCELE & 15# SALT. 200 SKS CLASS C WITH 2% CaCl<sub>2</sub>.

DEPTH OF FLOAT COLLAR - 4951.57

DEPTH OF CASING SHOE - 4999.20

DV TOOL - 3214.21

COMMENTS CIRCULATED 232 SKS TO SURFACE.

PRODUCTION STRING: 7 7/8" HOLE WAS DRILLED FROM 5000' TO 6247'. SET 5 1/2" 20 AND 23# CSG. 6247.70. CEMENTED WITH 425 SKS CLASS H PREMIUM PLUS WITH 5# KCL AND 4/10% HALAD 322 PER SACK. ESTIMATED TOP OF CEMENT, 4500'.

18. I hereby certify that the foregoing is true and correct

SIGNED Danny Brown

TITLE OPERATIONS MANAGER

DATE 1/23/89

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE  
FEB 7 1989

\*See Instructions on Reverse Side

CARLSBAD, <sup>SJS</sup>NEW MEXICO