
FOR: OXY USA INC., SNYDER RANCH A 1; LEA, NM

WELL ID: 1401318 HAS DRILL STEM TEST REPORT ON 2/26/89

DRILL STEM TEST	(FROM) - (TO)	FORMATION	TYPE TEST
DST NUMBER 1 9446 9328	BONE SPRING	CONV OH	
M.D. 9446 TVD	SIZE 7.875 MUD WT 9.4	VISCOSITY 41.0	
DP OD SIZE 4.500 DC 6.250 ID 2.250 LG 828	FLUID SURF	MIN	
1ST 2ND	ASSEMBLY RECORDER, PERF	SUB, SUB, 2 DC'S,	
INIT FLOW TM 15 MN 15 MN	SUB, PERF SUB, 2 PKRS,	SAFETY JT, JARS	
IHP 4614 4725	TOP PACKER 9322	BTM PKR 9328	
ISIP 3645 3726	CUSHION TYPE	AMOUNT	
IFP			
FFTM 60 HRMN 60 HRMN	BH TEMPERATURE 138	BH CHOKE 0.937	
FFP	REC. LENGTH 200	OF SGCM	
FSIP 3645 3726	REC. LENGTH 7200	OF SALT WATER	
FHP 4614 4688	REC. LENGTH	OF	
FSI TIME 120 HRMN 120 HRMN	REC. LENGTH	OF	
FLOWED GAS OIL WATER	HRMN FTP		
FLOWED GAS OIL WATER	HRMN FTP		
TIME OPENED 00 : 00 CLOSED 00 : 00	DRILL STEM TIME START 00 : 00	END 00 : 00	
OIL GR	GAS GVTY	WATER SP GRAVITY	

DST REMARKS:

* CIRC SUB, 15 DC'S.

IFP 1ST: 260-1644, 2ND: 390-1764

FFP 1ST: 1644-3582, 2ND: 1764-3638

CHLORIDES TOP OF TOOL = 105,000 PPM. TOP CIRC SUB = 105,000

PPM. TOP OF RECOVERY = 79,000 PPM. PIT SAMPLE = 81,000 PPM

SAMPLE CHAMBER CONTAINED 0.1 CUFT GAS, 2300 CC FORM WATER @

350 PSIG WATER RESISTIVITY = 0.22 OHMS @ 64 DEG F.