

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Budget Bureau No. 1004
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL

LC-064194

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

POWELL FEDERAL

9. WELL NO.

2

10. FIELD AND POOL OR WILDCAT

QUAIL RIDGE-DELAWARE

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

SEC. 4 T20S-R34E

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR
BILL FENN, INC.
3. ADDRESS OF OPERATOR
P. O. DRAWER 569, GIDDINGS, TEXAS 78942
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
1650' FSL & 1650' FEL

14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3631.8 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

DRILLED A 8 3/4" HOLE TO TD - 5,865' - DID NOT SET 7"

PLUG TO ABANDON THE ABOVE CAPTIONED WELL AS PER BLM REQUIREMENTS - 7-25-89

PLUG #1	5500 - 5700' (TOP OF DELAWARE)	DID NOT TAG	100 SACKS
PLUG #2	3110 - 3260' (BASE OF SALT)	3088 T	180 SACKS
PLUG #3	1525 - 1675' (CASING SHOE)	1301 T	150 SACKS
Plug #4	0 - 60'	SURFACE PLUG	20 SACKS

TYPE CEMENT USED: PREMIUM PLUS 'C' + 2% CaCl

INSTALLED DRY HOLE MARKER ON 7-26-89 AS REQUIRED

18. I hereby certify that the foregoing is true and correct

SIGNED

Danny Brown

TITLE OPERATIONS MANAGER

DATE 8/3/89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.
Liaison for BLM and USFS until
8/24/89

*See Instructions on Reverse Side

RECEIVED