

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30814
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name AMERICAN NATIONAL KEOHANE GAS COM.
8. Well No. 2
9. Pool name or Wildcat EUMONT YATES 7 RIVERS (PRO GAS)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. Name of Operator TEXACO INC.	
3. Address of Operator P. O. Box 3109 Midland, Texas 79702	
4. Well Location Unit Letter <u>G</u> : <u>1830</u> Feet From The <u>NORTH</u> Line and <u>1800</u> Feet From The <u>EAST</u> Line Section <u>18</u> Township <u>19-SOUTH</u> Range <u>37-EAST</u> NMPM LEA County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3696', KB-3709'	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. DRILL 7 7/8 HOLE TO 3650'. TD AT 2:00pm 5-23-90.
2. HALLIBURTON RAN GR-DLL-MG & GR-SDL-CNL FROM 3650' TO 1300'. GR TO SURFACE.
3. RAN 90 JTS OF 5 1/2, 15.5#, K-55, LT&C CSG. SET AT 3650'.
4. HALLIBURTON CEMENTED w/ 500 SX 35/65 POZ CLASS H w/ 6% GEL, 5% SALT & 1/4# FLOCELE @ 12.8ppg. F/B 250 SX CLASS H @ 15.6ppg. PLUG DOWN AT 1:45pm 5-24-90. CIRC 25 SX.
5. RELEASED RIG AT 7:00pm 5-24-90.
6. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C. P. Basham TITLE DRILLING SUPERINTENDENT DATE 05-29-90  
TYPE OR PRINT NAME C. P. BASHAM TELEPHONE NO. 915-6884620

(This space for State Use)

Orig. Signed by  
Paul Kautz  
Geologist

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE JUN 01 1990

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
MAY 31 1996  
GUC  
FBIHQ OFFICE