

Sample	Depth	Grain Dens	Poro sity	Kv	Permeability Max.	90	Sw	So	Flo	Remarks
67		3747	2.81	6.1	0.01	22.63	19.62	68.3	0.0	0 Dolo, Sandy, S/P, Sty, Fr.
68		3748	2.81	5.8	<.01	<.01	Plug	51.2	22.2	30 Sand, Gray, Dolom, S/P
69		3748.5	2.70	12.6	0.34	0.48	0.21	61.9	16.9	Sp.90 Sand, Gray, Dolom, S/P
	3748.5	3749	SCAL							
70	3749	3750	2.71	13.3	*0.27	1.55	Plug	36.1	27.1	100 Sand, Gray, Dolom, S/P, Brkn.
71		3751	2.67	18.7	*6.14	3.65	Plug	31.2	26.7	100 Sand, Gray, Dolom, Brkn.
72		3752	2.70	14.0	0.07	0.47	0.43	30.2	21.1	100 Sand, Gray, Dolom, S/P, Brkn.
73		3753	2.72	12.9	0.39	0.25	0.24	30.5	20.3	100 Sand, Gray, Dolom.
74		3754	2.76	7.5	0.01	0.14	0.08	43.4	28.2	30 Sand, Gray, Dolom.
75	3754	3755	2.68	15.3	0.05	0.49	0.37	33.3	19.5	100 Sand, Gray, Dolom.
76		3756	2.70	10.5	0.02	0.16	0.14	60.2	4.3	Sp.30 Sand, Gray, Dolom, Silty
77		3757	2.70	12.2	0.09	0.57	0.24	40.3	12.4	Sp.90 Sand, Gray, Dolom, Silty, S/P
78		3758	2.72	10.6	0.10	0.26	0.15	50.2	5.0	Sp.20 Sand, Gray, Dolom, Silty, S/P
79		3759	2.75	8.6	0.01	0.06	0.04	47.1	7.8	Sp.80 Sand, Gray, Dolom, Silty, S/P
80	3759	3760	2.73	7.6	0.01	0.23	0.18	76.4	0.0	Sp.30 Sand, Gray, Dolom, Shaly, Lam. S/P
81		3761	2.71	9.4	0.12	0.45	0.31	74.4	0.0	0 Sand, Gray, Dolom, S/P
82		3762	2.70	9.7	0.10	0.47	0.35	46.1	15.4	0 Sand, Gray, Dolom, S/P
83		3763	2.80	5.7	0.02	0.41	0.05	70.9	0.0	Lam30 Dolo, Sli. Shaly, Sandy, S/P
84		3764	2.78	6.2	0.01	0.25	0.21	73.6	0.0	Lam20 Dolo, Sli. Shaly, Sandy, S/P
85	3764	3765	2.72	11.2	0.04	0.25	0.18	45.7	8.6	Lam50 Sand, Gray, Dolom, S/P
86		3766	2.72	7.7	0.11	0.31	0.13	77.8	0.0	30 Sand, Gray, Dolom.
87		3767	2.84	4.8	0.01	0.13	0.08	76.8	0.0	TrB/O Dolo, S/P, Sty, Vt. Fr.
88		3768	2.85	2.4	*<.01	0.02	Plug	89.6	0.0	TrB/O Dolo, S/P, Sty, Vt. Fr.
89		3769	2.83	4.0	*0.01	0.32	0.10	55.1	18.4	TrB/O Dolo, S/P, Vt. Fr.
90	3769	3770	2.76	7.0	<.01	0.06	0.05	78.5	0.0	TrB/O Dolo, Sandy, Silty, S/P
91		3771	2.65	12.9	T/B	0.29	Plug	30.7	5.8	60 Sand, Gray, Dolom.
92	3771	3772	2.66	13.1	T/B	0.32	Plug	28.7	4.3	Sp.50 Sand, Gray, Dolom, Fr, Brkn.
			Core # (2)	3772-3864,	Cut 92',	Recovered 92'				
93	3772	3773	2.70	11.5	0.02	0.18	0.13	44.6	10.1	100 Sand, Gray, S/P
94		3774	2.77	7.8	0.02	0.07	0.07	55.0	13.7	50 Dolo, Sandy, Sli. Silty, S/P, Lrg. Sand Strg, Fr.
95	3774	3775	2.86	3.0	0.13	15.87	0.23	60.8	Tr.	TrB/O Dolo, Silty, S/P, Sty, Fr.
96		3776	2.85	1.6	0.03	0.11	0.03	77.7	0.0	TrB/O Dolo, Silty, S/P, Sty, Vt. Fr.
97		3777	2.82	4.4	0.03	0.33	0.03	77.3	0.0	Sp.20 Dolo, S/P, Lrg. Sh. Strg, Vt. Fr.
98		3778	2.79	5.4	<.01	0.09	0.07	80.1	0.0	Sp.30 Dolo, Silty, Sli. Shaly, Sc. Lam. S/P, Vt. Fr.
99		3779	2.79	6.0	0.01	0.10	0.07	71.6	16.5	TrB/O Dolo, Sli. Shaly, Sc. Lam. S/P, Vt. Fr.
100	3779	3780	2.74	10.2	0.02	0.34	0.24	50.5	10.1	50 Dolo, Sandy, Sli. Shaly, Sc. Lam. S/P, Lrg. Sd. Strg, Lrg. S
	3780	3780.5	SCAL							
101		3781	2.71	12.0	0.04	0.39	0.30	29.8	11.2	100 Sand, Gray, Dolom.