

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons.
P.O. Box 1980
Hobbs, NM 8824

Division FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
NM 55983

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Leo 30 Federal Com #1

9. API Well No.
30-025-31338

10. Field and Pool, or Exploratory Area
Osudo Morrow, North

11. County or Parish, State
Lea County, New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Nearburg Producing Company

3. Address and Telephone No.
P. O. Box 823085, Dallas, Texas 75382-3085 (214) 739-1778

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1,980' FSL and 1,650' FEL, Section 30, T19S, R36E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION	
☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☐ Subsequent Report	☐ Recompletion	☐ New Construction
☒ Final Abandonment Notice	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut-Off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other	☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Date Plugged & Abandoned: 1/16/97

- 1) Set CIBP @ 6,100'. Capped with 32' of cement.
- 2) Circulated BLM quality mud between all plugs.
- 3) Cut 5 1/2" casing @ 1,899'. Recovered casing.
- 4) Spotted 100' cement plug at 4,050' - 4,150'.
- 5) Spotted 210' cement plug from 1,730' - 1,940'. Tagged plug @ 1,770'.
- 6) Spotted 100' cement plug from 359' - 459'. Cut off wellhead.
- 7) Spotted 50' cement plug from surface - 50'.
- 8) Erected dry hole marker & cleaned location.



Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct.

Signed *Alexis C. Swoboda* Title Senior Engineer Date 2.10.97

(This space for Federal or State office use)

Approved by (ORIG. SGD.) ALEXIS C. SWOBODA Title PETROLEUM ENGINEER Date FEB 19 1997

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.