

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-31502

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

AMERADA HESS CORPORATION

3. Address of Operator

DRAWER D, MONUMENT, NM 88265

4. Well Location

Unit Letter K : 1980 Feet From The WEST Line and 1929' Feet From The SOUTH Line

Section 33

Township 19S

Range 37E

NMPM LEA

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3560' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: COMPLETION - PROGRESS REPORT ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-27 thru 9-19-92

MIRU DA&S OIL WELL SER. PULLING UNIT & TOH WITH 4-3/4" BIT. CHECKED CEMENT AT 4078' & DRLD. CEMENT, FLOAT COLLAR AT 4091' & CEMENT TO TD AT 4138'. CIRC. CSG. CLEAN & PRESS. TESTED 5-1/2" CSG. TO 1000#. HELD OK. SCHLUMBERGER RAN CEMENT BOND LOG FR. 4137'-100'. TIH WITH 5-1/2" CIBP & SET AT 4132'. SCHLUMBERGER RAN 4" HYPER JET III HOLLOW POINT CARRIER GUN & PERF. EUNICE MONUMENT G/SA ZONE W/1 SPF AT FOLLOWING: 4050', 4055', 4062', 4066', 4070', 4082', 4086', 4092', 4096', 4104', 4108', 4116', 4122' & 4128', TOTAL 14 HOLES. TIH WITH 5-1/2" PPI PKR. KNOX SER. ACIDIZED G/SA ZONE FR. 4050'-4128' W/950 GALS. 15% NEFE ACID. SWABBED WELL. RAN BHP BOMB. TOH W/PKR. HALLIBURTON SER. RAN 5-1/2" EZ-DRILL CEMENT RETAINER & JET AT 4040'. EST. INJ. RATE INTO PERFS. CEMENT SQUEEZED PERFS. FR. 4050'-4128' W/200 SKS. CLASS "C" NEAT CEMENT. REVERSED OUT 59 SKS., LEFT 8.5 SKS. IN CSG. & 132.5 SKS. IN FORMATION. SERFCO SPOTTED 2 BBLs. 15% NEFE ACID FR. 4028'-3944'. SCHLUMBERGER RAN 4" HYPER JET III HOLLOW POINT CARRIER GUN & PERF. EUNICE MONUMENT G/SA ZONE W/2 SPF AT FOLLOWING: 4006', 4013', 4018' & 4028', TOTAL 8 HOLES. TIH W/PPI PKR. ACIDIZED G/SA ZONE

CONTINUED ON BACK.....

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

R. L. Wheeler, Jr.

TITLE

Supv. Adm. Svc.

DATE

9-23-92

TYPE OR PRINT NAME

R. L. Wheeler, Jr.

TELEPHONE NO. 505 393-2144

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT SUPERVISOR

APPROVED BY

TITLE

DATE

SEP 23 '92

CONDITIONS OF APPROVAL, IF ANY:

CSG. PERF. FR. 4006'-4028' W/550 GAL. 15% NEFE ACID. SWABBED WELL. RAN BHP BOMB. TOH W/PKR. HALLIBURTON RAN 5-1/2" CEMENT RETAINER & SET AT 3991'. EST. INJ. RATE INTO CSG. PERFS. CEMENT SQUEEZED 5-1/2" CSG. PERFS. FR. 4006'-4028' W/100 SKS. CLASS "C" NEAT CEMENT. LEFT 1 SK. IN CSG., REVERSED OUT 59 SKS. & PUMPED 40 SKS. INTO FORMATION. WESTERN SPOTTED 2 BBLs. 15% NEFE ACID FR. 3960'-3886'. SCHLUMBERGER RAN 4" HYPER JET III HOLLOW POINT CARRIER GUN & PERF. EUNICE MONUMENT G/SA ZONE FR. 3950'-3960' W/2 SPF TOTAL 23 HOLES. TIH WITH 5-1/2" PKR. & SET AT 3834'. SWABBED WELL. RELEASED PKR. & SET AT 3960'. WESTERN CO. ACIDIZED G/SA ZONE 5-1/2" CSG. PERF. FR. 3950'-3960' WITH 750 GALS. 15% NEFE ACID. SWABBED WELL. RAN BHP BOMB. TOH WITH PKR. HALLIBURTON RAN 5-1/2" CEMENT RETAINER & SET AT 3940'. CEMENT SQUEEZED 5-1/2" CSG. PERFS. FR. 3950'-3960' W/200 SKS. CLASS "C" NEAT CEMENT. REVERSED OUT 41 SKS., LEFT 2 SKS. IN CSG. & PUMPED 157 SKS. INTO FORMATION. WESTERN CO. SPOTTED 2 BBLs. 15% NEFE ACID FR. 3927'-3843'. SCHLUMBERGER RAN 4" HYPER JET III HOLLOW POINT CARRIER GUN & PERF. EUNICE MONUMENT G/SA ZONE FR. 3908'-3932' W/2 SPF, TOTAL 49 HOLES. SWABBED WELL. TIH WITH 5-1/2" PKR. & ACIDIZED G/SA ZONE 5-1/2" CSG. PERF. FR. 3932'-3908' W/1,470 GAL. 15% NEFE ACID. SWABBED WELL & WELL BEGAN FLOWING. RAN BHP BOMB. KILLED WELL & TOH W/PKR. TIH WITH 5-1/2" BAKER LOK-SET RBP & SET AT 3904'. LOADED 5-1/2" CSG. & PRESS. RBP TO 1500#. HELD OK. SERFCO SPOTTED 7' SAND ON TOP RBP. PBD AT 3897'. SPOTTED 2 BBLs. 15% NEFE ACID FR. 3888'-3804'. SCHLUMBERGER PERF. EUNICE MONUMENT G/SA ZONE FR. 3888'-3868' W/4" HYPER JET III HOLLOW POINT CARRIER GUN W/2 SPF, TOTAL 41 HOLES. SWABBED WELL. TIH WITH 5-1/2" PPI PKR. & ACIDIZED G/SA ZONE 5-1/2" CSG. PERF. FR. 3888'-3868' W/1500 GALS. 15% NEFE ACID. SWABBED WELL & WELL STARTED FLOWING ON 9/19/92. FLOWING AT RATE OF 72 B.O., 528 B.W., & 1,000 MCFPD IN 24 HRS. ON 32/64" CHOKE. CONNECTED TO WARREN SALES LINE ON 9/19/92, 4:00 P.M.

10/19/92

10/19/92

10/19/92