

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31502
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER INJECTION	7. Lease Name or Unit Agreement Name NORTH MONUMENT GRAYBURG SAN ANDRES UNIT BLK 17
2. Name of Operator AMERADA HESS CORPORATION	8. Well No. 11
3. Address of Operator P. O. BOX 2040, TULSA, OKLA. 74102	9. Pool name or Wildcat EUNICE MONUMENT G/SA
4. Well Location Unit Letter K : 1929 Feet From The SOUTH Line and 1980 Feet From The WEST Line Section 33 Township 19S Range 37E NMPM LEA County	10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

SET 100 JTS. (4136.00') 5-1/2" CSG. AS FOLLOWS: 7 JTS. 5-1/2" 17# L-80 BUTT ERW "A" CSG. 1 JT. 5-1/2" 17# J-55 X-0 SMLS 8RL BOX X BUTT PIN, 8 JTS. 5-1/2" 17# L-80 8RL & 84 JTS OF 5-1/2" 14# K-55 8RS IN 7-7/8" HOLE @ 4136'.

B.J. CEMENTED W/420 SX C LITE + 5 #/SX A-5 + 1/4 #/SX CELLOFLAKE, SW=12.5 PPG., SY=2.04 CU.FT./SX. TAILED WITH 225 SX 50:50:2 (FA:C:GEL), + 3% A-9 + .9% FL-20 + 0.2% FR8 + 1/4 #/SX CELLOFLAKE, SW=14.4 PPG, SY=1.22 CU.FT./SX. RECIPROCATED CSG, HAD FULL RETURNS. BUMPED PLUG W/1750 PSI, PLUG DOWN @ 10:30 A.M. MDT, 07-08-92. INSTALLED TUBING HEAD AND TESTED TO 2500 PSI, RIG RELEASED @ 4:00 P.M. MDT. 07-08-92.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J. R. Wilson TITLE SUPERVISOR, DRLG ADMIN SVS. DATE 07-24-92
J. R. WILSON

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT I SUPERVISOR TITLE _____ DATE JUL 28 '92

CONDITIONS OF APPROVAL, IF ANY: