

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-31584

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL WELL ☐

GAS WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South Fourth Street - Artesia, NM 88210

4. Well Location

Unit Letter L : 2310 Feet From The South Line and 990 Feet From The West Line

Section 1

Township 20S

Range 32E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3485' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☒

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Yates Petroleum Corporation respectfully requests permission to change plans as follows:

FROM:

26" hole with 20" 94# casing set at 1145' with 1200 sacks of cement circulated
17-1/2" hole with 13-3/8" 54.5# casing set at 3100' with 1500 sacks of cement circulated
11" hole with 8-5/8" 32# casing set at 4400' with 2400 sacks of cement circulated*
7-7/8" hole with 5-1/2" 17# & 20# casing set at TD (7850') with enough cement to tie back

TO:

26" hole with 20" 94# casing set at 1145' with 1200 sacks of cement circulated,
17-1/2" hole with 13-3/8" 54.5# casing set at 3100' with 1500 sacks of cement circulated,
12-1/4" hole with 9-5/8" 36# casing set at 4400' with 2400 sacks of cement circulated*
8-3/4" hole with 7" 23# & 26# or 5-1/2" 15.5# & 17# casing set at TD (7850') with enough cement to tie back

*If lost circulation does not occur, will not run 9-5/8" casing, but will reduce hole and drill to TD with 8-3/4" hole.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk

DATE 9-19-94

TYPE OR PRINT NAME Rusty Klein

505-748-1471
TELEPHONE NO.

(This space for State Use)

Orig. Signed by
Paul Houtz
Geologist

SEP 20 1994

APPROVED BY

TITLE

DATE

RECEIVED

SEP 20 1994

**FOR THE
OFFICE**