

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-31584

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Snyder AKY Com

8. Well No.

1

9. Pool name or Wildcat

~~Wildcat Morrow~~ E. Lusk Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South Fourth Street - Artesia, NM 88210

4. Well Location

Unit Letter L : 2310 Feet From The South Line and 990 Feet From The West Line

Section 1

Township 20S

Range 32E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3485' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 1097'. Reached TD at 7:15 AM 9-14-94. Ran 28 joints of 20" casing as follows: 22 joints of 20" 106.5# J-55 ST&C and 6 joints of 20" 94# J-55 ST&C (1102.08') of casing set at 1097'. 1-Texas Pattern notched guide shoe set at 1097'. Insert float set at 1058.84'. Cemented with 1500 sacks Pacesetter Lite, 1/4#/sack celloseal and 2% CaCl2 (yield 2.01, weight 12.4). Tailed in with 300 sacks Class C 2% CaCl2 (yield 1.32, weight 14.8). PD 7:00 PM 9-14-94. Circulated 250 sacks. WOC. Drilled out at 6:30 PM 9-15-94. WOC 23 hours and 30 minutes. Reduced hole to 17-1/2". Resumed drilling. NOTE: Tested hydril to 1000 psi and tested casing to 1000 psi.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Production Clerk

DATE 9-16-94

TYPE OR PRINT NAME

Rusty Klein

505-748-1471
TELEPHONE NO.

(This space for State Use) **CRIG** **CRIG** **CRIG**

APPROVED BY

TITLE

DATE

SEP 20 1994

RECEIVED

SEP 19 1994

**JOE HODDS
OFFICE**