

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-025-31585

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
B-2052-3

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator  
AMERADA HESS CORPORATION

3. Address of Operator  
DRAWER D, MONUMENT, NM 88265

4. Well Location  
Unit Letter F : 2605 Feet From The NORTH Line and 2630 Feet From The WEST Line  
Section 19 Township 19S Range 37E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: PERFORATED & ACIDIZED ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1/28/93 THRU 2/26/93

MIRU X-PERT WELL SER. PULLING UNIT. TOH W/RODS & PUMP. NIPPLE DOWN WELLHEAD & INSTALLED BOP. TOH WITH 2-7/8" TBG., & 7" X 2-7/8" TAC. TIH & LATCHED ONTO BP. RELEASED & MOVED BP TO 3854'. CIRC. HOLE W/FRESH WATER & PRESS. BP TO 900 PSI. DUMPED 2 SKS. OF SAND DOWN CASING. RIGGED UP SCHLUMBERGER. TAGGED SAND AT 3849'. PERF. 7" CSG. W/4" GUN LOADED W/HYPER JET III CHARGES BETWEEN 3814' - 3822' AT 2 SPF. TOTAL 17 HOLES. TIH W/BAKER PPI PACKER SET AT 3824'. TESTED TO 3000 PSI. MOVED PKR. TO 3822'. DROPPED SPOT CONTROL VALVE. OPENED CONTROL VALVE & SPOTTED 600 GALS. NEFE 15% DI HCL ACID W/3% CHAMPION DP77MX CHEMICAL TO PERFS. SWABBED WELL. TOH WITH 2-7/8" TBG. & 7" X 2-7/8" PPI TOOL. TIH W/PFT TOOL, SN & 120 JTS. OF 2-7/8" TBG. RIGGED UP SERFCO TOOL AT 3825'. BROKE CIRC. WITH 46 BBLs. FRESH WATER. WASHED PERFS. W/WATER WHILE SPOTTING 700 GALS. 15% NEFE DI HCL ACID W/3% (CONT)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Cindy Robertson TITLE SR. ADMIN. STAFF ASSIST. DATE 4/14/93  
TYPE OR PRINT NAME CINDY ROBERTSON TELEPHONE NO. 393-2144

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT SUPERVISOR

APR 15 1993

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: