Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

CONDITIONS OF APPROVAL, IF ANY:

OIL CONSERVATION DIVISION
P.O. Box 2088

P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088 5. Indicate Type DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410 6. State Oil & G B-1167-4	31587
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: OTHER WATER SUPPLY 1. Name of Operator AMERADA HESS CORPORATION 1. Name of Operator ATTN: ONSHORE DRLG. SVS. 1. 201 LOUISIANA, SUITE 700, HOUSTON, TX. 77002 1. Well Location Unia Letter C: 80.5 Feet From The NORTH Lise and 1505 Feet From The North Price	of Lesse
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE 'APPLICATION FOR PERMIT' (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: OLD WILL ONS AMERADA HESS CORPORATION Address of Operator AMERADA HESS CORPORATION Address of Operator ATTN: ONSHORE DRLG. SVS. 1201 LOUISIANA, SUITE 700, HOUSTON, TX. 77002 Well Location Unit Letter C : 80.5 Feet From The NORTH Line and 1505 Feet From Total Louisian North Market Complete Comp	STATE X FEE
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR. USE 'APPLICATION FOR PERMIT' (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: OX.	18
Name of Operator AMERADA HESS CORPORATION Address of Operator ATTN: ONSHORE DRLG. SVS. 1201 LOUISTANA, SUITE 700, HOUSTON, TX. 77002 Well Location Unit Letter C: 80.5 Feet From The NORTH Line and 1505 Feet From Section 36 Township 19S Range 36E NMPM I Section 36 Township 19S Range 36E NMPM I NOTICE OF INTENTION TO: SUBSEQUENT FREE NOTICE OF INTENTION TO: SUB	or Unit Agreement Name ONUMENT GRAYBURG RES UNIT BLOCK 14
AMERADA HESS CORPORATION Address of Operator ATTN: ONSHORE DRLG. SVS. 1201 LOUISIANA, SUITE 700, HOUSTON, TX. 77002 Well Location Unit Letter C: 80.5 Feet From The NORTH Line and 1505 Feet From Section 36 Township 19S Range 36E NMFM I. 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3609.6 GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other NOTICE OF INTENTION TO: REFORM REMEDIAL WORK PLUG AND ABANDON GREMENT JOB X LL OR ALTER CASING OTHER: Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date work) SEE RULE 1103. CRACE DRILLING SPUD AN 17-1/2" HOLE AT 8:00 P.M. 07/25/92. SET 27 J. 48# H-40 8RS ERW R-3 CLASS "A" CASING IN A 17-1/2" HOLE. B.J. SERVI SXS CLASS "C" LITE + 10#/SX A-5, 1/4#/SX C.F., SW = 128, SY = 1.99. CLASS "C" + 2% A-7, SW = 14.8 PPG, SY = 1.32 CU.FT./SX. CIRC. 45 SX PLUG DOWN AT 4:00 P.M. 07/27/92. TEST CASING W1/200 PSI FOR 30 MINU JTS (3641') 9-5/8" 36# K-55 ERW R-3 "A" CASING IN A 12-1/4" HOLE. B.CEMENTED WITH 650 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F.,	
Address of Operator ATTN: ONSHORE DRLG. SVS. 1201 LOUISIANA, SUITE 700, HOUSTON, TX. 77002 Well Location Unit Letter C: 80.5 Feet From The NORTH Line and 1505 Feet From Section 36 Township 19S Runge 36E NMPM LINE Section 36 Township 19S Runge 36E NMPM LINE SECTION 3609.6 GR Check Appropriate Box to Indicate Nature of Notice, Report, or Othe NOTICE OF INTENTION TO: RFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. X LL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB X BER ULE 1103. GRACE DRILLING SPUD AN 17-1/2" HOLE AT 8:00 P.M. 07/25/92. SET 27 J 48# H-40 8RS ERW R-3 CLASS "C" L12* A-7, SW = 14.8 PPG, SY = 1.32 CU.FT./SX. CIRC. 45 SX PLUG DOWN AT 4:00 P.M. 07/27/92. TEST CASING W/1200 PSI FOR 30 MINU JTS (3641') 9-5/8" 36# K-55 ERW R-3 "A" CASING IN A 12-1/4" HOLE. B CEMENTED WITH 650 SXS CLASS "C" L1TE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" L2* A-7, SW = 14.8 PPG, SY = 1.32 CU.FT./SX. CIRC. 45 SX PLUG DWITH 275 SXS CLASS "C" L1TE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" L1TE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" L2* A-7, SW = 14.8, SY = 1.32. PLUG 08/01/92. TESTED CASING TO 1500 PSI FOR 30 MINUTES, O.K. SET 38 JT 8RL ERW R-3 CLASS "A" CASING IN A 8-3/4" HOLE. B.J. SERVICES CEMENT "C" 50:50:2 + 5#/SX A-5 + 0.4% FL-20 + 0.2% A-2 + 0.2% CD-31 + 1/4#/SY SY = 1.35. PLUG DOWN AT 3:30 P.M. 08/19/92. FLOATS HELD, RELEASED OVER TO PRODUCTION FOR COMPLETION.	
Well Location Unit Letter C: 80.5 Feet From The NORTH Line and 1505 Feet From Section 36 Township 19S Range 36E NMPM L 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3609.6 GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other NOTICE OF INTENTION TO: REFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. X LL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB X CASING TEST AND CEMENT JOB X CASING TEST AND CEMENT JOB X OTHER: Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date work) SEE RULE 1103. GRACE DRILLING SPUD AN 17-1/2" HOLE AT 8:00 P.M. 07/25/92. SET 27 J 48# H-40 8RS ERW R-3 CLASS "A" CASING IN A 17-1/2" HOLE. B.J. SERVI SSS CLASS "C" LITE + 10#/SX A-5, 1/4#/SX C.F., SW = 128, SY = 1.99. CLASS "C" + 2% A-7, SW = 14.8 PPG, SY = 1.32 CU.FT./SX. CIRC. 45 SX PLUG DOWN AT 4:00 P.M. 07/27/92. TEST CASING W/1200 PSI FOR 30 MINU JTS (3641') 9-5/8" 36# K-55 ERW R-3 "A" CASING IN A 12-1/4" HOLE. B. CEMENTED WITH 650 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SY = 1.32. PLUG 08/01/92. TESTED CASING TO 1500 PSI FOR 30 MINUTES, O.K. SET 38 JT 3RL ERW R-3 CLASS "A" CASING IN A 8-3/4" HOLE. B.J. SERVICES CEMENT "C" 50:50:2 + 5#/SX A-5 + 0.4% FL-20 + 0.2% A-2 + 0.2% CD-31 + 1/4#/SY = 1.35. PLUG DOWN AT 3:30 P.M. 08/19/92. FLOATS HELD, RELEASED OVER TO PRODUCTION FOR COMPLETION. Dereby certify that the information above is true and complete to the best of my knowledge and belief.	Wildcat
Unit Letter C: 80.5 Feet From The NORTH Line and 1505 Feet From Section 36 Township 19S Range 36E NMPM INC. Elevation (Show whether DF, RKB, RT, GR, etc.) 3609.6 GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other NOTICE OF INTENTION TO: SUBSEQUENT FOR SU	MONUMENT G/SA
Check Appropriate Box to Indicate Nature of Notice, Report, or Other NOTICE OF INTENTION TO: SUBSEQUENT FRORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB X CASING TEST AND CEMENT JOB X	m The WEST Line LEA County
Check Appropriate Box to Indicate Nature of Notice, Report, or Othe NOTICE OF INTENTION TO: SUBSEQUENT STANDARD SUBSEQUENT SUBSEQUENT SUBSEQUENCE SUB	<i>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</i>
NOTICE OF INTENTION TO: REFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JOB CASING TEST AND CEMENT JOB THER: Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date work) SEE RULE 1103. GRACE DRILLING SPUD AN 17-1/2" HOLE AT 8:00 P.M. 07/25/92. SET 27 J 48# H-40 8RS ERW R-3 CLASS "A" CASING IN A 17-1/2" HOLE. B.J. SERVI SXS CLASS "C" LITE + 10#/SX A-5, 1/4#/SX C.F., SW = 128, SY = 1.99. CLASS "C" L2% A-7, SW = 14.8 PPG, SY = 1.32 CU.FT./SX. CIRC. 45 SX PLUG DOWN AT 4:00 P.M. 07/27/92. TEST CASING W/1200 PSI FOR 30 MINU JTS (3641') 9-5/8" 36# K-55 ERW R-3 "A" CASING IN A 12-1/4" HOLE. B CEMENTED WITH 650 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" + 2% A-7, SW = 14.8, SY = 1.32. PLUG 08/01/92. TESTED CASING TO 1500 PSI FOR 30 MINUTES, O.K. SET 38 JT 8RL ERW R-3 CLASS "A" CASING IN A 8-3/4" HOLE. B.J. SERVICES CEMENT "C" 50:50:2 + 5#/SX A-5 + 0.4% FL-20 + 0.2% A-2 + 0.2% CD-31 + 1/4#/SY = 1.35. PLUG DOWN AT 3:30 P.M. 08/19/92. FLOATS HELD, RELEASED OVER TO PRODUCTION FOR COMPLETION.	r Data
COMMENCE DRILLING OPNS. X LL OR ALTER CASING HER: DTHER: DTHER: DTHER	
CASING TEST AND CEMENT JOB X HER: DOTHER: DOT	ALTERING CASING
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date work) SEE RULE 1103. GRACE DRILLING SPUD AN 17-1/2" HOLE AT 8:00 P.M. 07/25/92. SET 27 J 48# H-40 8RS ERW R-3 CLASS "A" CASING IN A 17-1/2" HOLE. B.J. SERVI SXS CLASS "C" LITE + 10#/SX A-5, 1/4#/SX C.F., SW = 128, SY = 1.99. CLASS "C" + 2% A-7, SW = 14.8 PPG, SY = 1.32 CU.FT./SX. CIRC. 45 SX PLUG DOWN AT 4:00 P.M. 07/27/92. TEST CASING W/1200 PSI FOR 30 MINU JTS (3641') 9-5/8" 36# K-55 ERW R-3 "A" CASING IN A 12-1/4" HOLE. B CEMENTED WITH 650 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" + 2% A-7, SW = 14.8, SY = 1.32. PLUG 08/01/92. TESTED CASING TO 1500 PSI FOR 30 MINUTES, O.K. SET 38 JT 8RL ERW R-3 CLASS "A" CASING IN A 8-3/4" HOLE. B.J. SERVICES CEMENT "C" 50:50:2 + 5#/SX A-5 + 0.4% FL-20 + 0.2% A-2 + 0.2% CD-31 + 1/4#/SY = 1.35. PLUG DOWN AT 3:30 P.M. 08/19/92. FLOATS HELD, RELEASED OVER TO PRODUCTION FOR COMPLETION.	PLUG AND ABANDONMENT
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date work) SEE RULE 1103. GRACE DRILLING SPUD AN 17-1/2" HOLE AT 8:00 P.M. 07/25/92. SET 27 J 48# H-40 8RS ERW R-3 CLASS "A" CASING IN A 17-1/2" HOLE. B.J. SERVI SXS CLASS "C" LITE + 10#/SX A-5, 1/4#/SX C.F., SW = 128, SY = 1.99. CLASS "C" + 2% A-7, SW = 14.8 PPG, SY = 1.32 CU.FT./SX. CIRC. 45 SX PLUG DOWN AT 4:00 P.M. 07/27/92. TEST CASING W/1200 PSI FOR 30 MINU JTS (3641') 9-5/8" 36# K-55 ERW R-3 "A" CASING IN A 12-1/4" HOLE. B CEMENTED WITH 650 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" + 2% A-7, SW = 14.8, SY = 1.32. PLUG 08/01/92. TESTED CASING TO 1500 PSI FOR 30 MINUTES, 0.K. SET 38 JT 8RL ERW R-3 CLASS "A" CASING IN A 8-3/4" HOLE. B.J. SERVICES CEMENT "C" 50:50:2 + 5#/SX A-5 + 0.4% FL-20 + 0.2% A-2 + 0.2% CD-31 + 1/4#/SY = 1.35. PLUG DOWN AT 3:30 P.M. 08/19/92. FLOATS HELD, RELEASED OVER TO PRODUCTION FOR COMPLETION. hereby certify that the information showe is true and complete to the best of my knowledge and belief.	
GRACE DRILLING SPUD AN 17-1/2" HOLE AT 8:00 P.M. 07/25/92. SET 27 J 48# H-40 8RS ERW R-3 CLASS "A" CASING IN A 17-1/2" HOLE. B.J. SERVI SXS CLASS "C" LITE + 10#/SX A-5, 1/4#/SX C.F., SW = 128, SY = 1.99. CLASS "C" + 2% A-7, SW = 14.8 PPG, SY = 1.32 CU.FT./SX. CIRC. 45 SX PLUG DOWN AT 4:00 P.M. 07/27/92. TEST CASING W/1200 PSI FOR 30 MINU JTS (3641') 9-5/8" 36# K-55 ERW R-3 "A" CASING IN A 12-1/4" HOLE. B CEMENTED WITH 650 SXS CLASS "C" LITE + 10#/SX A-5 + 1/4#/SX C.F., SW TAILED WITH 275 SXS CLASS "C" + 2% A-7, SW = 14.8, SY = 1.32. PLUG 08/01/92. TESTED CASING TO 1500 PSI FOR 30 MINUTES, O.K. SET 38 JT 8RL ERW R-3 CLASS "A" CASING IN A 8-3/4" HOLE. B.J. SERVICES CEMENT "C" 50:50:2 + 5#/SX A-5 + 0.4% FL-20 + 0.2% A-2 + 0.2% CD-31 + 1/4#/SY = 1.35. PLUG DOWN AT 3:30 P.M. 08/19/92. FLOATS HELD, RELEASED OVER TO PRODUCTION FOR COMPLETION.	
hereby certify that the information above is true and complete to the best of my knowledge and belief.	TTS. (1185') 13-3/8" TCES CEMENTED W/615 TAILED W/300 SXS TELLED W/300 SXS TELLE
Pater 11/1/11	DATE 8-28-92
TYPE OR PRINT NAME BUSY WILLIAMS	TELEPHONE NO. //3) 658-91