

DISTRICT I

P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

| | |
|--|--|
| WELL API NO. | 30-025-31589 |
| 5. Indicate Type of Lease | STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. | B-218-1 |
| 7. Lease Name or Unit Agreement Name North Monument G/SA Unit Blk. 10 | |
| 8. Well No. | 22 |
| 9. Pool name or Wildcat Eunice Monument G/SA | |

| | |
|---|--|
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | |
| 1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | |
| 2. Name of Operator Amerada Hess Corporation | |
| 3. Address of Operator P. O. Box 840, Seminole, Texas 79360 | |
| 4. Well Location Unit Letter <u>F</u> : <u>2567</u> Feet From The <u>North</u> Line and <u>1330</u> Feet From The <u>West</u> Line Section <u>30</u> Township <u>19S</u> Range <u>37E</u> NMPM Lea County | |
| 10. Elevation (Show whether DF, RKB, RT, GR, etc.) | |

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-1 thru 2-7-2000

MRIU Key Energy Svc. pulling unit & TOH w/rods & pump. Removed wellhead, installed BOP & TOH w/tbg. TIH w/CIBP & set at 3910'. Baker Atlas perf. Grayburg San Andres Zone using 4" csg. gun w/2 SPF, total 58 shots, fr. 3860' - 3888'. Halliburton Svc. acidized perfs. fr. 3789' - 3888' w/2000 gal. 15% NEFE HCL acid w/500# 50/50 rock salt. Swabbed well. TIH w/2-7/8" tbg. set at 3878'. Removed BOP & installed wellhead. TIH w/pump & rods. RDP, cleaned location, & continued producing well.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roy L. Wheeler, Jr. TITLE Bus. Svc. Spec. II DATE 2-14-2000
TYPE OR PRINT NAME Roy L. Wheeler, Jr. TELEPHONE NO. 915 758-6700

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: