

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

WELL API NO.	30-025-31589
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil & Gas Lease No.	B-218-1

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐	7. Lease Name or Unit Agreement Name NORTH MONUMENT G/SA UNIT BLK. 10			
b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DEEP RESVR ☐ OTHER ☐	8. Well No. 22			
2. Name of Operator AMERADA HESS CORPORATION	9. Pool name or Wildcat EUNICE MONUMENT G/SA			
3. Address of Operator DRAWER D, MONUMENT, NEW MEXICO 88265				
4. Well Location Unit Letter <u>F</u> : <u>2,567</u> Feet From The <u>NORTH</u> Line and <u>1,330</u> Feet From The <u>WEST</u> Line Section <u>30</u> Township <u>19S</u> Range <u>37E</u> NMPM LEA County				
10. Date Spudded 8/27/92	11. Date T.D. Reached 9/14/92	12. Date Compl. (Ready to Prod.) 1/29/93	13. Elevations (DFA RKB, RT, GR, etc.) 3633.7 GR	14. Elev. Casinghead
15. Total Depth 4,500'	16. Plug Back T.D. 3,959'	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By Rotary Tools X	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name 3,882'-3,898' & fr. 3,914'-3,924' GRAYBURG SAN ANDRES				20. Was Directional Survey Made YES
21. Type Electric and Other Logs Run DLL/MSFL/CAL/LDT/CNL/EPT/NGT/FMI/SONIC/GR/MDT				22. Was Well Cored YES

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	48#	427'	17-1/2"	400 SX. CLASS "C"	
9-5/8"	36#	3,646'	12-1/4"	805 SX. CLASS "C" & 695 SX. CLASS "H"	
7"	20# & 26#	4,500'	8-3/4"	250 SX. CLASS "C" LITE & C	

24. LINER RECORD				25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SIZE	DEPTH SET	PACKER SET
				2-7/8"	3,933'	

26. Perforation record (interval, size, and number)
PERF. FR. 3,914'-3,924' w/4" CSG. GUN W/2 JSPF
TOTAL 21 SHOTS
PERF. FR. 3,882'-3,898' w/4" CSG. GUN W/2 JSPF
TOTAL 33 HOLES

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.
DEPTH INTERVAL
3,914'-3,924' ACID. W/1500 GALS. 15% DINEFE
W/ 3% DP77MX MICELLAR SOLVENT.
3,882'-3,898' ACID. W/800 GALS. 15% NEFE
W/3% DP77MX CHEMICAL.

28. PRODUCTION

Date First Production 1/29/93	Production Method (Flowing, gas lift, pumping - Size and type pump) PUMPING 2-1/4" x 4' METAL PLUNGER				Well Status (Prod. or Shut-in) PRODUCING		
Date of Test 2/7/93	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl. 10	Gas - MCF 27	Water - Bbl. 480	Gas - Oil Ratio 2,700
Flow Tubing Press. 0	Casing Pressure 45#	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
SOLD

Test Witnessed By

30. List Attachments

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature R. L. Wheeler, Jr. Printed Name R. L. Wheeler, Jr. Title Supv. Adm. Svc. Date 2-10-93

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____	T. Canyon _____
T. Salt _____ 1,323'	T. Strawn _____
B. Salt _____ 2,470'	T. Atoka _____
T. Yates _____	T. Miss _____
T. 7 Rivers _____	T. Devonian _____
T. Queen _____	T. Silurian _____
T. Grayburg _____ 3,616'	T. Montoya _____
T. San Andres _____ 3,954'	T. Simpson _____
T. Glorieta _____	T. McKee _____
T. Paddock _____	T. Ellenburger _____
T. Blinbry _____	T. Gr. Wash _____
T. Tubb _____	T. Delaware Sand _____
T. Drinkard _____	T. Bone Springs _____
T. Abo _____	T. _____
T. Wolfcamp _____	T. _____
T. Penn _____	T. _____
T. Cisco (Bough C) _____	T. _____

Northwestern New Mexico

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Otzte _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. _____
T. Morrison _____	T. _____
T. Todilto _____	T. _____
T. Entrada _____	T. _____
T. Wingate _____	T. _____
T. Chinle _____	T. _____
T. Permian _____	T. _____
T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____	No. 3, from _____ to _____
No. 2, from _____ to _____	No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____	feet _____
No. 2, from _____ to _____	feet _____
No. 3, from _____ to _____	feet _____

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
1,213'	1,323'	110'	Anhydrite				
1,323'	2,470'	1147'	Salt				
2,470'	3,412'	942'	Sand, Dolomite & Anhydrite				
3,412'	3,618'	206'	Sand & Dolomite				
3,618'	4,500'	882'	Dolomite with sand stringers				