

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-31589
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	B-218-1

7. Lease Name or Unit Agreement Name	North Monument Grayburg San Andres Unit BLK 10
8. Well No.	22
9. Pool name or Wildcat	Eunice Monument G/SA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator Amerada Hess Corporation	
3. Address of Operator Attn: Drlg Svc., 1201 Louisiana, Ste 700, Houston, TX 77002	
4. Well Location Unit Letter F : 2567 Feet From The North Line and 1330 Feet From The West Line Section 30 Township 19 S Range 37 E NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3633.7	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 103 jts (4500') 7" K-55 in 8 3/4" hole as follows: 90 jts (3925') 7" 20# K-55 ERW R-3 ST&C and 13 jts (575') 7" 26# K-55 R-3 LT&C. BJ Services cemented with 75 SXS. C Lite + 5#/sk A-5 + 1/4#/sk CF. SW=12.5, SY=2.04. Tailed with 175 SXS Class "C" + 3% A-9 + 0.9% FL-20 + 0.2% FP-8 + 1/4#/sk CF. SW=14.4, SY=1.22. Plug on bottom at 11:50 p.m. on 9/16/92. Floats held. Released rig and turned well over to production for completion.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Betsy Williams TITLE Petroleum Engineer DATE 9/21/92  
TYPE OR PRINT NAME Betsy Williams TELEPHONE NO. (713) 752-5437

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE SEP 28 '92  
CONDITIONS OF APPROVAL, IF ANY: