

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

U. S. DEPT. OF THE INTERIOR
P. O. BOX 1000
HOBBS, NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well ☒ Oil Well ☐ Gas Well ☐ Other	5. Lease Designation and Serial No. NM 13280
2. Name of Operator Devon Energy Corporation (Nevada)	6. If Indian, Allotment or Tribe Name NA
3. Address and Telephone No. 20 North Broadway, Suite 1500, OKC, OK 73102 (405) 235-3611	7. If Unit or CA, Agreement Designation NA
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 2250' FSL & 2014' FWL, Section 11-20S-33E	8. Well Name and No. Smith Ranch "11" Fed. #2
	9. API Well No. 30-025-31683
	10. Field and Pool, or Exploratory Area Teas Bone Springs
	11. County or Parish, State Lea County, NM

Unit K

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Resumption	☐ New Construction
☐ Final Abandonment Notice	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut-Off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other Spud and set surface casing	☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Resumption Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

07-27-93 Set 40' of 20" conductor pipe. Began moving in Midessa Drilling Company, Rig #1.

07-29-93 SPUD 17 1/2" hole at 1500 hrs.

08-01-93 Ran 13 3/8" csg as follows.
34 jts 13 3/8" 54.5# J55 8rd csg (1400')
guide shoe set at 1400', float collar at 1314'

08-01-93 Cemented 13 3/8" csg as follows.
900 sx 65/35 w/6% gel, 1/4#/sx Flocele; mixed at 12.4 ppg= 1.979 yield; +
200 sx Class C w/2% cc; mixed at 14.8 ppg= 1.32 yield.
Circ'd 108 sx cement to surface.
Job completed at 1700 hrs.

14. I hereby certify that the foregoing is true and correct		E.L. Buttross, Jr. District Engineer		/cg	Date 8/4/93
Signed <u>E.L. Buttross Jr.</u>					
(This space for Federal or State office use)					
Approved by _____		Title _____		Date <u>8/7/1993</u>	
Continued on approval, if any:					

RECEIVED

SEP 09 1993

COMMUNICATIONS
OFFICE