

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31688
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-1587
7. Lease Name or Unit Agreement Name Pearl 29
8. Well No. 1
9. Pool name or Wildcat Pearl San Andres, West

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator Matador Operating Co.	
3. Address of Operator 415 W. Wall, Ste 1101, Midland, TX 79701	
4. Well Location Unit Letter <u>N</u> : <u>330</u> Feet From The <u>South</u> Line and <u>1650</u> Feet From The <u>West</u> Line Section <u>29</u> Township <u>19S</u> Range <u>35E</u> NMPM <u>Lea</u> County <u></u>	
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole @ 7:30 PM (MST) 10-8-92. Drilled 12-1/4" hole to 431' KB. Ran 10 jts 8-5/8", 24#, J-55, ST&C new casing. Set @ 430' KB. Halliburton cemented w/325 sx Class C cement, 2% CaCl2, 1/4 #/sk Flocele. Displaced w/fresh water. Circ 120 sx cement to pit. PD @ 9:00 AM 10-9-92. Float held. Pressure csg to 1000 psi and holds OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. F. Burke TITLE Operations Manager DATE 10-12-92
TYPE OR PRINT NAME R. F. Burke TELEPHONE NO. 915-687-5955

(This space for State Use) ORIGINAL SIGNED BY RAY SMITH

APPROVED BY RAY SMITH TITLE DATE 10-12-92

CONDITIONS OF APPROVAL, IF ANY: