

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31832
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-9062
7. Lease Name or Unit Agreement Name LITTLE EDDY UNIT
8. Well No. 1
9. Pool name or Wildcat HAT MESA - BONE SPRINGS

10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3634' GL
--

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
BASS ENTERPRISES PRODUCTION CO.

3. Address of Operator
P O BOX 2760; MIDLAND, TX 79702-2760

4. Well Location
Unit Letter M : 330 Feet From The SOUTH Line and 990 Feet From The WEST Line
Section 32 Township 20S Range 33E NMMPM LEA County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: SPUD-DATE SURFACE & INTERMEDIATE CASING ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

SPUD 7:45 PM MST 12-25-92
DRILL 14 3/4" HOLE TO 1,313', RAN 30 JTS 11 3/4" 42# H-40
ST&C CSG SET @ 1313'. CEMENTED W/805SX CLASS "C" CEMENT WITH ADDITIVES. CIRCULATED 225SX TO SURFACE. PLUG DOWN 7:50 PM MST.
1-2-93 WOC 20 3/4 HRS. TEST BLIND RAMS TO 1500' OK. TEST PIPE RAMS TO 1500' OK. DRILL FLOAT COLLAR & CEMENT, TEST TO 600 PSI OK. DRILL SHOE & 10' FORMATION TEST TO 600 PSI OK.
DRILL 11" HOLE TO 3,177' 1-5-93.
RAN - 58 JTS 8 5/8" 24# K-55 ST&C & 17 JTS 8 5/8" 24# S-80 ST&C. SET @ 3177' CEMENTED W/1000SX PACESETTER LITE & CLASS "C" WITH ADDITIVES. CIRCULATED 185SX TO PIT.
WOC 22 3/4 HRS.
TEST BOPE TO 3000 PSI OK.
DRILL FLOAT COLLAR & CEMENT, TEST CSG TO 1000 PSI OK. DRILL SHOE AND 10' OF FORMATION & TEST TO 1000 PSI OK.
DRILL 7 7/8" HOLE 1-6-93.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R.C. Houtchens R.C. HOUTCHENS TITLE SENIOR PRODUCTION CLERK DATE 1-7-93

TYPE OR PRINT NAME TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

JAN 11 1993

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: