

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. OIL CONS. COMMISSION
P.C. BOX 1980
HOBBS, NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Read & Stevens, Inc.

3. Address and Telephone No.

P. O. Box 1518 Roswell, NM 505/622-3770

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FSL & 330' FEL
Section 3 T20S-R34E

5. Lease Designation and Serial No.

NM-54432

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Mark Federal #8

9. API Well No.

30-025-32158

10. Field and Pool or Exploratory Area

Quail Ridge Delaware

11. County or Parish, State

Lea County NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other Perforations
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/07/93

Set RBP @ 5,779' & perforate 5,698'-5,708', 5,716'-5,727', w/ 44 holes. Acidize w/ 1,000 gal of 7 1/2% NEFE & frac w/ 16,500 gal of cross linked gel & 43,000# of 16/30 sand. Tested 1 BO, 0 MCF & 100 BW in 24 hrs. Set CIR @ 5,649' & squeeze cmt perfs 5,698'-5,727' w/ 75 sx of Class "C" low wtr loss cmt. Drill out CIR & cmt, test csg & squeeze perfs to 800 psi for 30 min-held OK. Rls RBP & pull to 5,648' & set. Perforate 5,548'-5,552', 5,562'-5,572', 30 holes. Acidize w/ 800 gal of 7 1/2% NEFE & frac w/ 14,000 gal of cross linked gel & 47,000# of 16/30 sand. Pump tested 0 BO, 0 MCF & 20 BW in 24 hrs. Very small trace of oil. Shut well in for evaluation.

14. I hereby certify that the foregoing is true and correct

Signed

John C. Maxey

Title Petroleum Engineer

Date 3-7-94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

J. Lara
MAR 20 1994

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side