

FORM C-103

BERTHA BARBER #13-14

PAGE 2 OF 2

9-13-94

PRESET 14" CONDUCTOR @ 40' & CMT'D TO SURF W/ REDI-MIX. MIRU NORTON #4, SPUD 8-3/4" HOLE @ 0445 HRS 8-12-94. DRLD TO 1208'. RAN 28 JTS 7", 26#, K-55, LTC CSG TO 1208'. TX PATTERN SHOE @ 1206', FLOAT COLLAR @ 1165'. CMT'D SURF CSG W/ 115 SX PSL "C" W/ 6% GEL, 2% CACL₂, 1/4#/SK CELLOFLAKE. TAILED IN W/ 150 SX CLASS "C" W/ 2% CACL₂. PLUG DN @ 0330 HRS 8-13-94, CIRC'D 45 SX TO PIT. WOC. CUT 7" CSG. WELD ON 7" CSG HEAD. NU 11" 3M DUAL RAM BOPE, 3M ANNULAR, ROTATING HEAD & CHOKE MANIFOLD. TESTED RAMS, CHOKE & KILL LINES, MANIFOLD, KELLY COCKS & FLOOR VALVES TO 300/3000#. TESTED ANNULAR TO 200/2000#. PU 6-1/2" BIT & TAGGED CMT @ 1060'. TOTAL WOC 38.5 HRS. TESTED CSG TO 1500#. DRLD CMT & FLOAT COLLAR TO 1190'. TESTED SHOE JT TO 1500#. DRLD CMT & RESUMED DRLG FORMATION. DRLD 6-1/2" HOLE TO 3650'. LOGGED WELL AS FOLLOWS: DLL/CAL/MSFL/GR 3650'-SURF; LDT/CNL/GR 3650'-SURF. RAN 84 JTS 4-1/2", 10.5#, K-55 LTC CSG TO 3650'. SHOE @ 3649', FC @ 3568'. CMT'D W/ 425 SX "C" LITE W/ 6% GEL, 2% CACL₂ (12.7#, 2.03 Y). TAILED IN W/ 130 SX "C" W/ .2% CF-19 (14.8#, 1.23 Y). CIRC'D 61 SX CMT TO SURF. BUMPED PLUG, CIP @ 1700 HRS 8-19-94. SET SLIPS, CUT CSG, NU WH. RIG RELEASED @ 2400 HRS 8-19-94.