

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-32391
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	A-1543-1
7. Lease Name or Unit Agreement Name	(000143) NORTH MONUMENT GRAYBURG SAN ANDRES UNIT BLK. 9
8. Well No.	10
9. Pool name or Wildcat	(23000) EUNICE MONUMENT G/SA

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE 'APPLICATION FOR PERMIT' (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:	OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator	AMERADA HESS CORPORATION (000495)
3. Address of Operator	DRAWER D, MONUMENT, NEW MEXICO 88265
4. Well Location	

Unit Letter J : 1915 Feet From The SOUTH Line and 1843 Feet From The EAST Line

Section 25 Township 19S Range 36E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3639.5' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	
OTHER: <input type="checkbox"/>	

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <u>NEW WELL COMPLETION</u> <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

NMGSAU #910
3-17 THRU 4-5-94

MIRU PULLING UNIT & INSTALLED BOP. TIH W/6-1/4" MILL & MILLED OUT DV TOOL FR. 2027'-2029' & TOH. RAN 6-1/4" BIT TAGGED UP AT 3890' & DRLD. TO TD AT 4142'. CIRC. HOLE CLEAN. TIH W/7" X 2-7/8" BAKER LOK-SET RBP & SET AT 3800'. LOADED HOLE & PRESS. TO 1000 PSI. HELD OK. DUMPED 3 SKS. SAND ON TOP RBP. SCHLUMBERGER RAN CBL FR. 3733' TO TOP OF CEMENT AT 120'. TIH W/RETRIEVING TOOL, WASHED SAND OFF RBP, LATCHED ONTO & TOH W/RBP. HALLIBURTON CIRC. 10 BBLs. FRESH WATER & SPOTTED 25 SKS. PREMIUM PLUS CEMENT W/2 LBS. PER SACK CAL-SEAL, 1 LB. PER SACK KCL & 5% HALAD-344 FROM 4142'-3984'. TIH & TAGGED CEMENT PLUG AT 4054'. TIH W/FTI SONIC HAMMER & ACIDIZED OH FR. 4040'-3830' W/3000 GAL. 15% NEFE HCL ACID CONTAINING 3% DP-77-MX CHEMICAL. TOH W/TBG. & TOOL. TIH W/PKR. SET AT 3805' & SWABBED WELL. HALLIBURTON PLUGGED BACK OH FR. 4054'-3994' W/5 SKS. PREMIUM CEMENT CONTAINING 2% (CON'T ON BACK)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. L. Wheeler, Jr. TITLE SUPV. ADM. SVC. DATE 4-20-94
TYPE OR PRINT NAME R.L. WHEELER, JR. TELEPHONE NO. (505) 393-2147

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE MAY 02 1994

CONDITIONS OF APPROVAL, IF ANY:

CAL-SEAL, 1 LB. PER SACK KCL & 5% HALE-344. RAN TBG. & REVERSED OUT CEMENT FR. 3994'-4006'. SWABBED WELL. RAN TBG. & TAGGED BOTTOM AT 4042'. TIH W/PKR. SET AT 3804' & SWABBED WELL. TOH W/PKR. TIH W/7" X 2-7/8" BAKER TAC ON 3-7/8" TBG. SET SN OE AT 4001' & TAC AT 3772' W/14,000 PSI TENSION. REMOVED BOP, INSTALLED WELLHEAD & TIH W/20 X 150 X RWBC 16-4-S-O PUMP ON RODS. RDPU & CLEANED LOCATION. SET PUMPING UNIT & MOTOR. CONNECTED ELECTRICAL SERVICE & BEGAN PUMPING WELL ON 4-5-94. WELL PRODUCING TO NMGS AU BATTERY NO. 35.

TEST OF 3-22-94: PUMPED 20 B.O., 111 B.W., & 25 MCFGPD IN 24 HRS.

RECEIVED

APR 23 1994

JOHN HOBBS
OFFICE