

06/02/94 10:04

C-1 505 393 0720

HUBBS OIL CONSRN

4002

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-101
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address: AMERADA HESS CORPORATION 1201 LOUISIANA, STE 700 HOUSTON, TEXAS 77002		ATTN: KEN WHITE	1 OGRID Number 000495
2 Property Code 000194	3 Property Name STATE "J" GAS COM		4 API Number 30-025-32533
			5 Well No. 6

7 Surface Location									
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	2	20S	36E		990'	SOUTH	990'	WEST	LEA

8 Proposed Bottom Hole Location If Different From Surface									
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
9 Proposed Pool 1 EUMONT YATES SEVEN RIVERS QUEEN					10 Proposed Pool 2				

11 Work Type Code N	12 Well Type Code G	13 Cable/Rotary M	14 Lease Type Code S	15 Ground Level Elevation 3600.3
16 Multiple NO	17 Proposed Depth 3600'	18 Formation SEVEN RIVERS QUEEN	19 Contractor UNKNOWN	20 Spud Date 6-21-94

21 Proposed Casing and Cement Program					
Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
11"	8-5/8"	24#	400'	125	SURF
7-7/8"	5-1/2"	15.5#	3600'	700	SURF


Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

DRILL 11" HOLE TO 400' AND SET 400' OF 24# 8-5/8" SURF CSG. CEMENT WITH 125 SX 65/35 POZ AND CIRCULATE TO SURFACE.

DRILL 7-7/8" HOLE TO 3600' AND SET 3600' OF 5-1/2" 15.5# PRODUCTION CSG. CEMENT CSG WITH 700 SX CLASS "C" CEMENT AND CIRCULATE TO SURFACE.

I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature:



Printed name:

KEN WHITE

Title:

SUPVSR, DRLG SVS

Date:

OIL CONSERVATION DIVISION

Approved by:

Title:

Approval Date:

JUN 08 1994

Expiration Date: