N.M. OIL CONS. COMMISSION P.O. BOX 1980 HOBBS, NEW MEXICO 88240

Form 3160-5 (June 1990)

or representations as to any matter within its jurisdiction.

UNITED STATES

FORM APPROVED

Budget Bureau No. 1004-0135
Expires: March 31, 1993
Lease Designation and Serial No.

	ENT OF THE INTERIOR F LAND MANAGEMENT	Expires: March 31, 1993 5. Lease Designation and Serial No.
SUNDRY NOTICE	S AND DEPOSTS ON MELLS	LC 031622A
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals		6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well		
Oil Well Well Other 2. Name of Operator Conoco Inc 3. Address and Telephone No.		8. Well Name and No.
		SANDERSON 'A' #18 9. API Well No.
10 Desta Drive STE 100W. Midland, TX 79705 (915)686-5424		30-025-32574 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		EUMONT YATES 7 RVRS QN
1980 FSL & 1920 FEL, SEC 11, T-20S, R-36E, UNIT LTR 'J'		
12. CHECK APPROPRIATE BOX	X(s) TO INDICATE NATURE OF NOTICE, REPOR	LEA, NM RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
Subsequent Report	Recompletion Plugging Back	New Construction Non-Routine Fracturing
Final Abandonment Notice	Casing Repair Altering Casing XMher SPUD, SET SURFACE CSG	Water Shut-Off Conversion to Injection
		Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
 Describe Proposed or Completed Operations (Clearly state give subsurface locations and measured and true ver 	all pertinent details, and give pertinent dates, including estimated date of starting rucal depths for all markers and zones pertinent to this work.)*	any proposed work. If well is directionally drilled.
7-27-94 SPUD @ 7 pm 12 1/4" HO SET @ 430 SHOE SET @ 430 CACL2. TAIL SLURRY 150 SX CLA OF 68 SX. NOTIFIED BLM @ 7 pm 7-28-94 CONTINUE DRILLING 7 7/	LE. DRILL TO 430°. GIH W/ 10 JTS 8 5/8 COLLAR SET @ 384°. LEAD SLURRY 230 SX S C + 2% CACL2. DISPLACED W/ 25 bbl ON 7 26-94. 8" HOLE.	" 24# K-55 STC CSG CLASS C + 4% GFC + 2% FW. CEMENT RETURNS
·		2-11 3-11 1-11 1-11
		2 **
•	Y Law	
	7 / 3 *	
		<u>12.1</u>
		Co. 1
		# mill
		e reger
14. I hereby certify that the foregoing is true and correct	CD PEGULATORY CAPE	
Signed First Laurel	Title SR. REGULATORY SPEC	B-1-94
(This space for Federal or State office use)		B-1-94
Signed First Laurel	Title SR. REGULATORY SPEC	Date