Form 3160-5 (June 1990)

L...TED STATES DEPARTMENT OF THE INTERIOR

N. M. OIL CONS. COMMISSION

Ρ.	BO	X 19	30 EURY	4 ADDROVEDA A
MIP.S	anc.	NEW	MEXI	CON 18 1240.

EAL HORBS	NEW MEXILLY NO ROLL
'ENEWED	Expires: March 31, 1993 5. Lease Designation and Serial N

	BUREAU OF	5. Lease Designation and Serial No.	
	SUNDRY NOTICES	LC 064194	
Do not	use this form for proposals to d	6. If Indian, Allottee or Tribe Name	
	Use "APPLICATION FO	R PERMIT—" for such proposals II 95	
	SUBMI	7. If Unit or CA, Agreement Designation	
l Type of V			
2. Name of 0		8. Well Name and No.	
	on Oil Company of Califo	Unocal "8" Federal #1	
	nd Telephone No.	30-025-32821	
P. (O. Box 671 - Midland, TX	10. Field and Pool, or Exploratory Area	
4. Location of	of Well (Footage, Sec., T., R., M., or Survey D	Quail Ridge Morrow (gas)	
M30 660	' FWL & 1980' FNL - Sec.	9 m20c p24p	11. County or Parish, State
1/2 000	TWE & 1900 FILE - Sec.	0, 1205, R34E	
			Lea County, N. Mexico
12.	CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
	TYPE OF SUBMISSION	TYPE OF ACTION	
		THE OF ACTION	
	Source of Intent	Abandonment	Change of Plans
	Subsequent Report	Recompletion	New Construction
	Subsequent Report	Plugging Back	Non-Routine Fracturing
	Final Abandonment Notice	Casing Repair Altering Casing	Water Shut-Off
	The Adaptive House	Spud & run csg	Conversion to Injection Dispose Water
			(Note: Report results of multiple completion on Well
			Completion or Recompletion Report and Log form.)
13. Describe F	Proposed or Completed Operations (Clearly state a	pertinent details, and give pertinent dates, including estimated date of starting	any proposed work. If well is directionally drilled
13. Describe F	subsurface locations and measured and true verti-	Il pertinent details, and give pertinent dates, including estimated date of starting cal depths for all markers and zones pertinent to this work.)*	any proposed work. If well is directionally drilled,
give :	subsurface locations and measured and true vertices. CONTACTED TAMMY W/ B	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIG	any proposed work. If well is directionally drilled,
give :	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIG UDIT. SET 40' OF 20" COND PIPE CMTD W	any proposed work. If well is directionally drilled, #356. HELD SAFETY #1/ 5 YDS OF READY
give :	subsurface locations and measured and true vertice CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIG	any proposed work. If well is directionally drilled, #356. HELD SAFETY #1/ 5 YDS OF READY
give : 5–21–95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS.	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIGUDIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ R . WL SURVEY (3/4 DEG @ 950'). DRLD TO	any proposed work. If well is directionally drilled. #356. HELD SAFETY #/ 5 YDS OF READY RPT TIME W/ NO 0 1072'/2 HRS. TOH
-21-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIGUDIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ R . WL SURVEY (3/4 DEG @ 950'). DRLD TO ED UP). JET SHALE PIT. TIH, WASH 55'	any proposed work. If well is directionally drilled. #356. HELD SAFETY #/ 5 YDS OF READY RPT TIME W/ NO 0 1072'/2 HRS. TOH
give : -21-95 -22-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIGUDIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F WL SURVEY (3/4 DEG @ 950'). DRLD TO ED UP). JET SHALE PIT. TIH, WASH 55' 112'/13 HRS. LE @ 1534' @ 12:15 PM 5/23/95. NOWIET.	#356. HELD SAFETY #/ 5 YDS OF READY RPT TIME W/ NO 0 1072'/2 HRS. TOH TO BTM, NO
give : :-21-95 :-22-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIGUDIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F . WL SURVEY (3/4 DEG @ 950'). DRLD TO ED UP). JET SHALE PIT. TIH, WASH 55' 12'/13 HRS. LE @ 1534' @ 12:15 PM 5/23/95. NOTIFII TLER ANHY @ 1510'. CIRC & COND. DROP	any proposed work. If well is directionally drilled. #356. HELD SAFETY #/ 5 YDS OF READY RPT TIME W/ NO 0 1072'/2 HRS. TOH TO BTM, NO
13. Describe F give : 5-21-95 5-22-95 5-23-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH. NO DRAG.	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIGUDIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DECE SURVEY (3/4 DEG @ 950'). DRLD TO DECE SURVEY (3/4 DEG @ 950'). DRLD TO DECE SURVEY (3/4 DEG @ 950'). ED UP). JET SHALE PIT. TIH, WASH 55' LD 21:15 PM 5/23/95. NOTIFIED AND SET SURVEY (3/4 DEG COND. DROP). LD REAMERS. BU TO PUN CSC. SER BROWN.	any proposed work. If well is directionally drilled. #356. HELD SAFETY # 5 YDS OF READY RPT TIME W/ NO D 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @
give : -21-95 -22-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIGUDIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DECE UP). JET SHALE PIT. TIH, WASH 55' 12'/13 HRS. JE @ 1534' @ 12:15 PM 5/23/95. NOTIFITY TER ANHY @ 1510', CIRC & COND. DROP SET ANHY @ 1510', CIRC & COND. DROP SET ANHY @ 1510', CIRC & COND. SAFETY 54.5# J-55 LSS 8RD ST&C NEW ERW CSG @ 12.7 PPG (1.84 VIFID) F/B 300 SET ANHY BERN CSG & 12.7 PPG (1.84 VIFID) F/B 300 SET ANHY BERN CSG & 12.7 PPG (1.84 VIFID) F/B 300 SET ANHY BERN CSG & 12.7 PPG (1.84 VIFID) F/B 300 SET ANHY BERN CSG & 12.7 PPG (1.84 VIFID) F/B 300 SET ANHY BERN CSG & 12.7 PPG (1.84 VIFID) F/B 300 SET ANHY BERN CSG & 12.7 PPG (1.84 VIFID) F/B 300 SET ANHY BERN CSG & 12.7 PPG (1.84 VIFID) F/B 300 SET ANHY BERN CSG & 12.7 PPG (1.84 VIFID) F/B 300 SET ANHY BERN CSG & 12.7 PPG (1.84 VIFID) F/B 300 SET ANHY BER	any proposed work. If well is directionally drilled. #356. HELD SAFETY #/ 5 YDS OF READY RPT TIME W/ NO D 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX
give : -21-95 -22-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD)	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIGUDIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DECE UP). JET SHALE PIT. TIH, WASH 55' 12'/13 HRS. JE @ 1534' @ 12:15 PM 5/23/95. NOTIFITY CLER ANHY @ 1510', CIRC & COND. DROP: LD REAMERS. RU TO RUN CSG. SAFETY 54.5# J-55 LSS 8RD ST&C NEW ERW CSG @ 12.7 PPG (1.84 YIELD) F/B 300 SX "C. BEN BY	any proposed work. If well is directionally drilled. #356. HELD SAFETY #/ 5 YDS OF READY RPT TIME W/ NO 0 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 28 CACL2 @
give : 21-95 22-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD) W/ 230 BFW @ 8.5-3 BF	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIGUDIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DECENTED TO THE STANDARD PIT. TIH, WASH 55' ALZ'/13 HRS. JE @ 1534' @ 12:15 PM 5/23/95. NOTIFIED TO THE STANDARD PIT. LD REAMERS. RU TO RUN CSG. SAFETY SAME J-55 LSS SRD ST&C NEW ERW CSG @ 12.7 PPG (1.84 YIELD) F/B 300 SX TO TENDARD PIT. @ 7 BPH, 250-200 PSI. DISP RUBBER PIT. JE 240-570 PSI. RUMPED PIT.	any proposed work. If well is directionally drilled. # #356. HELD SAFETY # / 5 YDS OF READY RPT TIME W/ NO 0 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 2% CACL2 @ LUG TO FC @ 1487'
give : -21-95 -22-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD) W/ 230 BFW @ 8.5-3 BF	cal depths for all markers and zones pertinent to this work.)* LM @ 6:25 AM 5/21/95. MIRU NABORS RIGUDIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ FOLLOW COLD WITH COLD	any proposed work. If well is directionally drilled. #356. HELD SAFETY #/ 5 YDS OF READY RPT TIME W/ NO 0 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 2% CACL2 @ LUG TO FC @ 1487'
5–21–95 5–22–95 5–23–95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD) W/ 230 BFW @ 8.5-3 BF PD-CIP @ 10:15 PM 5/2 COND 13-3/8" CSG, INC	LM @ 6:25 AM 5/21/95. MIRU NABORS RIGULIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DEG	any proposed work. If well is directionally drilled. #356. HELD SAFETY #7 5 YDS OF READY RPT TIME W/ NO D 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 2% CACL2 @ LUG TO FC @ 1487' SI, FLOAT HELD. HRS. CUT OFF & -3/8" S/O W/ EFO
–21–95 –22–95 –23–95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD) W/ 230 BFW @ 8.5-3 BF PD-CIP @ 10:15 PM 5/2 COND 13-3/8" CSG, INC	LM @ 6:25 AM 5/21/95. MIRU NABORS RIGULIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DETE SHALE PIT. TIH, WASH 55' DI2'/13 HRS. LE @ 1534' @ 12:15 PM 5/23/95. NOTIFICATION OF SET ANHY @ 1510', CIRC & COND. DROP DETE SHALE PIT. TIH, WASH 55' DETE ANHY @ 1510', CIRC & COND. DROP DETE SHALE PIT. DISP RUBBER PIT. LD REAMERS. RU TO RUN CSG. SAFETY S4.5# J-55 LSS SRD ST&C NEW ERW CSG @ 12.7 PPG (1.84 YIELD) F/B 300 SX "C @ 7 BPH, 250-200 PSI. DISP RUBBER PITM, 240-570 PSI. BUMPED PLUG W/ 700 PSI DISP CIRC 274 SX CMT TO PIT. WOC 4 DETE SITE OF STATE	any proposed work. If well is directionally drilled. #356. HELD SAFETY #7 5 YDS OF READY RPT TIME W/ NO D 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 2% CACL2 @ LUG TO FC @ 1487' SI, FLOAT HELD. HRS. CUT OFF & 13/8" S/O W/ EFO ACK. CHK MANI TO
–21–95 –22–95 –23–95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD) W/ 230 BFW @ 8.5-3 BF PD-CIP @ 10:15 PM 5/2 COND 13-3/8" CSG, INC FIN CUT OFF 13-3/8" C CSG HD. NU BOP STACK	LM @ 6:25 AM 5/21/95. MIRU NABORS RIGULIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DEG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DEG AHEAD @ F. DUP). JET SHALE PIT. TIH, WASH 55' DI2'/13 HRS. E @ 1534' @ 12:15 PM 5/23/95. NOTIFINATE ANHY @ 1510', CIRC & COND. DROP: LD REAMERS. RU TO RUN CSG. SAFETY S4.5# J-55 LSS 8RD ST&C NEW ERW CSG @ E. 2.7 PPG (1.84 YIELD) F/B 300 SX "C. E. 2.7 PPG (1.84 YIELD) F/B 300 SX "C. E. 2.7 PPG (1.84 YIELD) F/B 300 SX "C. E. 3/95. CIRC 274 SX CMT TO PIT. WOC 4 DEG AMERICAN SET STANDARD PLUG W/ 700 PS. SG. WELD ON OCT C-22 13-5/8" 3M X 13-6 CHK MANI. TEST BLIND RAMS, BOP STANDARD AND STANDARD SHOCK SUB.	any proposed work. If well is directionally drilled. #356. HELD SAFETY #/ 5 YDS OF READY RPT TIME W/ NO D 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 2% CACL2 @ LUG TO FC @ 1487' SI, FLOAT HELD. HRS. CUT OFF & -3/8" S/O W/ EFO ACK, CHK MANI TO - (1) 8" DC, 3 PT
give : :-21-95 :-22-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD) W/ 230 BFW @ 8.5-3 BF PD-CIP @ 10:15 PM 5/2 COND 13-3/8" CSG, INC FIN CUT OFF 13-3/8" C CSG HD. NU BOP STACK 1000 PSI/30 MIN, OK. RMR. (2) 8" DC'S, 3 P	LM @ 6:25 AM 5/21/95. MIRU NABORS RIGULIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DETE SHALE PIT. TIH, WASH 55' DI2'/13 HRS. LE @ 1534' @ 12:15 PM 5/23/95. NOTIFICATION OF SET ANHY @ 1510', CIRC & COND. DROP DETE SHALE PIT. TIH, WASH 55' DETE ANHY @ 1510', CIRC & COND. DROP DETE SHALE PIT. TIH, WASH 55' DETE SHE SHOT DETE SHE COND. DROP DETE SHE SHE SHE COND. DROP DETE SHE DETE SHE COND. DROP DETE DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DETE DETE DETE DETE DETE DETE DETE DET	any proposed work. If well is directionally drilled. #356. HELD SAFETY #/ 5 YDS OF READY RPT TIME W/ NO D 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 2% CACL2 @ LUG TO FC @ 1487' SI, FLOAT HELD. HRS. CUT OFF & -3/8" S/O W/ EFO ACK, CHK MANI TO - (1) 8" DC, 3 PT
=21-95 =-22-95 =-23-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD) W/ 230 BFW @ 8.5-3 BF PD-CIP @ 10:15 PM 5/2 COND 13-3/8" CSG, INC FIN CUT OFF 13-3/8" C CSG HD. NU BOP STACK	LM @ 6:25 AM 5/21/95. MIRU NABORS RIGULIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DETE SHALE PIT. TIH, WASH 55' DI2'/13 HRS. LE @ 1534' @ 12:15 PM 5/23/95. NOTIFICATION OF SET ANHY @ 1510', CIRC & COND. DROP DETE SHALE PIT. TIH, WASH 55' DETE ANHY @ 1510', CIRC & COND. DROP DETE SHALE PIT. TIH, WASH 55' DETE SHE SHOT DETE SHE COND. DROP DETE SHE SHE SHE COND. DROP DETE SHE DETE SHE COND. DROP DETE DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DETE DETE DETE DETE DETE DETE DETE DET	any proposed work. If well is directionally drilled. #356. HELD SAFETY #/ 5 YDS OF READY RPT TIME W/ NO D 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 2% CACL2 @ LUG TO FC @ 1487' SI, FLOAT HELD. HRS. CUT OFF & -3/8" S/O W/ EFO ACK, CHK MANI TO - (1) 8" DC, 3 PT
=21-95 =-22-95 =-23-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD) W/ 230 BFW @ 8.5-3 BF PD-CIP @ 10:15 PM 5/2 COND 13-3/8" CSG, INC FIN CUT OFF 13-3/8" C CSG HD. NU BOP STACK 1000 PSI/30 MIN, OK. RMR. (2) 8" DC'S, 3 P	LM @ 6:25 AM 5/21/95. MIRU NABORS RIGULIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DETE SHALE PIT. TIH, WASH 55' DI2'/13 HRS. LE @ 1534' @ 12:15 PM 5/23/95. NOTIFICATION OF SET ANHY @ 1510', CIRC & COND. DROP DETE SHALE PIT. TIH, WASH 55' DETE ANHY @ 1510', CIRC & COND. DROP DETE SHALE PIT. TIH, WASH 55' DETE SHE SHOT DETE SHE COND. DROP DETE SHE SHE SHE COND. DROP DETE SHE DETE SHE COND. DROP DETE DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DETE DETE DETE DETE DETE DETE DETE DET	any proposed work. If well is directionally drilled. #356. HELD SAFETY #/ 5 YDS OF READY RPT TIME W/ NO D 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 2% CACL2 @ LUG TO FC @ 1487' SI, FLOAT HELD. HRS. CUT OFF & -3/8" S/O W/ EFO ACK, CHK MANI TO - (1) 8" DC, 3 PT
6-21-95 6-22-95 6-23-95 6-24-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD) W/ 230 BFW @ 8.5-3 BF PD-CIP @ 10:15 PM 5/2 COND 13-3/8" CSG, INC FIN CUT OFF 13-3/8" C CSG HD. NU BOP STACK 1000 PSI/30 MIN, OK. RMR, (2) 8" DC'S, 3 P CIRC. TESTING PIPE R	LM @ 6:25 AM 5/21/95. MIRU NABORS RIGULIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DEG DIP. JET SHALE PIT. TIH, WASH 55' DI2'/13 HRS. LE @ 1534' @ 12:15 PM 5/23/95. NOTIFINATION OF STATE ANHY @ 1510', CIRC & COND. DROP: LD REAMERS. RU TO RUN CSG. SAFETY 54.5# J-55 LSS 8RD ST&C NEW ERW CSG @ 12.7 PPG (1.84 YIELD) F/B 300 SX "C @ 7 BPH, 250-200 PSI. DISP RUBBER PIPM, 240-570 PSI. BUMPED PLUG W/ 700 PSI DISP. CIRC 274 SX CMT TO PIT. WOC 4 COND. SG. WELD ON OCT C-22 13-5/8" 3M X 13-6 CHK MANI. TEST BLIND RAMS, BOP STATIH W/ 12-1/4" ATJ33C BIT, SHOCK SUB, T RMR, (15) 8" DC'S, X-O, DP. TAGGED AMS, INC.	any proposed work. If well is directionally drilled. #356. HELD SAFETY #5 YDS OF READY RPT TIME W/ NO D 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 2% CACL2 @ LUG TO FC @ 1487' SI, FLOAT HELD. HRS. CUT OFF & -3/8" S/O W/ EFO ACK, CHK MANI TO (1) 8" DC, 3 PT @ 1486'. BRK
=21-95 =-22-95 =-23-95 =-24-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD) W/ 230 BFW @ 8.5-3 BF PD-CIP @ 10:15 PM 5/2 COND 13-3/8" CSG, INC FIN CUT OFF 13-3/8" C CSG HD. NU BOP STACK 1000 PSI/30 MIN, OK. RMR, (2) 8" DC'S, 3 P CIRC. TESTING PIPE R	LM @ 6:25 AM 5/21/95. MIRU NABORS RIGULIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DETE SHALE PIT. TIH, WASH 55' DI2'/13 HRS. LE @ 1534' @ 12:15 PM 5/23/95. NOTIFICATION OF SET ANHY @ 1510', CIRC & COND. DROP DETE SHALE PIT. TIH, WASH 55' DETE ANHY @ 1510', CIRC & COND. DROP DETE SHALE PIT. TIH, WASH 55' DETE SHE SHOT DETE SHE COND. DROP DETE SHE SHE SHE COND. DROP DETE SHE DETE SHE COND. DROP DETE DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DISP RUBBER PICK, 240-570 PSI. BUMPED PLUG W/ 700 PSI DETE DETE DETE DETE DETE DETE DETE DET	any proposed work. If well is directionally drilled. #356. HELD SAFETY #5 YDS OF READY RPT TIME W/ NO D 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 2% CACL2 @ LUG TO FC @ 1487' SI, FLOAT HELD. HRS. CUT OFF & -3/8" S/O W/ EFO ACK, CHK MANI TO -(1) 8" DC, 3 PT
21-95	CONTACTED TAMMY W/ B MTG & PRE-SPUD RIG A MIX. SPUD 17-1/2" H PROBLEMS. DRLD TO 996'/4.5 HRS. F/ BIT (2 CONES LOCKE PROBLEMS. DRLD TO 14 TD'D 17-1/2" SURF HOI 1:04 PM. TOP OF RUST 1450'. TOH, NO DRAG. 1 PC (1513') 13-3/8" "HLC" W/ 1/4# FLOCELE 14.8 PPG (1.32 YIELD) W/ 230 BFW @ 8.5-3 BF PD-CIP @ 10:15 PM 5/2 COND 13-3/8" CSG, INC FIN CUT OFF 13-3/8" C CSG HD. NU BOP STACK 1000 PSI/30 MIN, OK. RMR, (2) 8" DC'S, 3 P CIRC. TESTING PIPE R	LM @ 6:25 AM 5/21/95. MIRU NABORS RIGULIT. SET 40' OF 20" COND PIPE CMTD WOLE @ 7:00 PM 5/21/95. DRLG AHEAD @ F. WL SURVEY (3/4 DEG @ 950'). DRLD TO DEG DIP. JET SHALE PIT. TIH, WASH 55' DI2'/13 HRS. LE @ 1534' @ 12:15 PM 5/23/95. NOTIFINATION OF STATE ANHY @ 1510', CIRC & COND. DROP: LD REAMERS. RU TO RUN CSG. SAFETY 54.5# J-55 LSS 8RD ST&C NEW ERW CSG @ 12.7 PPG (1.84 YIELD) F/B 300 SX "C @ 7 BPH, 250-200 PSI. DISP RUBBER PIPM, 240-570 PSI. BUMPED PLUG W/ 700 PSI DISP. CIRC 274 SX CMT TO PIT. WOC 4 COND. SG. WELD ON OCT C-22 13-5/8" 3M X 13-6 CHK MANI. TEST BLIND RAMS, BOP STATIH W/ 12-1/4" ATJ33C BIT, SHOCK SUB, T RMR, (15) 8" DC'S, X-O, DP. TAGGED AMS, INC.	any proposed work. If well is directionally drilled. #356. HELD SAFETY #5 YDS OF READY RPT TIME W/ NO D 1072'/2 HRS. TOH TO BTM, NO ED KATHY W/ BLM @ SURVEY, 3/4 DEG @ MTG. R&S 33 JTS + 1534' W/ 940 SX C" W/ 2% CACL2 @ LUG TO FC @ 1487' SI, FLOAT HELD. HRS. CUT OFF & -3/8" S/O W/ EFO ACK, CHK MANI TO (1) 8" DC, 3 PT @ 1486'. BRK

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

